

## Resene Ceiling Paint Flat Acrylic

Resene Ceiling Paint is recommended for use on ceilings of living rooms, bedrooms and dining rooms where a flat finish is required. A very low odour, low spatter product.

### Interior Ceilings

#### Typical uses

- Fibrous plaster
- Paperfaced plasterboard
- Plaster glass
- Repaints

<b>Vehicle type</b>	100% acrylic
<b>Pigmentation</b>	Titanium dioxide
<b>Solvent</b>	Water
<b>Finish</b>	Flat
<b>Colour</b>	White
<b>Dry time</b>	45 minutes at 18°C
<b>Recoat</b>	2 hours minimum
<b>Sealer required</b>	Yes
<b>Theoretical coverage</b>	10 sq. metres per litre
<b>Dry film thickness</b>	34 microns at 10 sq. metres per litre
<b>Usual no. of coats</b>	1-2 coats
<b>Durability</b>	Good
<b>Thinning and clean up</b>	Water; in hot dry conditions can be thinned with up to 5% Resene Hot Weather Additive
<b>VOC</b>	c. 7 grams per litre (see <a href="#">Resene VOC Summary</a> )

#### Physical properties

#### Performance

#### Performance and limitations

#### Limitations

1. Inhibits mould growth.
2. Flow and build properties means that one coat is often enough to achieve complete hiding.
3. Excellent application properties with low spatter.
4. An Environmental Choice approved product.

1. Do not apply at temperatures below 10°C or when it is liable to drop below 10°C during the drying period.
2. Not recommended for use in bathrooms, kitchens or laundries (use Resene SpaceCote Flat – see [Data Sheet D314](#)).
3. Will not penetrate chalking and powdery surfaces.

# Ceiling Paint Flat Acrylic

## Surface preparation

### All surfaces

Ensure surface is dry and free from dirt, dust and loose material. Oil, grease and mould must be removed prior to painting. Fly spots and nicotine stains must be removed using Resene Emulsifiable Solvent Cleaner (see [Data Sheet D804](#)) or Sugar Soap.

Sand old glossy surfaces to provide a key for subsequent paint coats.

### New work, paperfaced plasterboard

Ensure new paperfaced plasterboard is prepared to a level of finish suitable for the specified paint finish. Resene Broadwall Surface Prep (see [Data Sheet D807](#)) or Resene Broadwall 3 in 1 (see [Data Sheet D810](#)) will be required to achieve a Level 5 finish. Seal Resene Broadwall Surface Prep (see [Data Sheet D807](#)) with Resene Broadwall Acrylic Wallboard Sealer (see [Data Sheet D403](#)) or Resene Sureseal (see [Data Sheet D42](#)).

Seal bare substrates as required.

*Sanding dust from old lead or chromate based paints or old building materials containing asbestos may be injurious to the health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.*

## Application

Stir thoroughly before use. Apply by brush, speed brush, synthetic fibre roller or spray. Apply one to two coats of Resene Ceiling Paint allowing two hours between coats under normal conditions.

## Precautions

Ensure correct sealer is used.

*Information contained in this Data Sheet is re-validated every two years following issue date.  
Please ensure current Data Sheet is consulted prior to specification or application of Resene products.  
If the surface you propose to coat is not referred to by this Data Sheet, please contact Resene for clarification.*