

Resene Paints Limited

32-50 Vogel Street
Naenae
Wellington
P O Box 38242
Wellington Mail Centre
NEW ZEALAND

Telephone: (64) (4) 577 0500
Fax: (64) (4) 577 0600
e-mail: advice@resene.co.nz
Emergency Phone: NZ 0800 737363
Emergency Phone: Aust. 1800 738383

MATERIAL SAFETY DATA SHEET

Version Number: 7
Date Issued: 15/10/2004

IDENTIFICATION

Product Name: ARMOURCHLOR HB-F
Other Names: FORMERLY HB CHLORINATED RUBBER
Description: PAINT
Uses: CHLORINATED RUBBER TOP COAT PROTECTIVE COATING

U N Number: 1263
Dangerous Goods Class: 3.3
Hazchem Code: 3[Y]
Toxic Substances Schedule: Fourth
Packing Code: III

Classification of Hazardous Nature:
Hazardous according to NZ Dangerous Goods and Toxic Substance Regulations.

Physical Description/Properties

Appearance-Viscosity-Odour-pH: Viscous white or coloured liquid, aromatic solvent odour.
Melting or Freezing Point: Not known
Boiling Point: Not known
Vapour Pressure (mm Hg @ 25 C): Not known
Vapour Density (Air=1): Greater Than 1
Solubility in Water (g/L @20 C): Less than 50
Percent Volatile (by weight): 51%
Specific Gravity (Water=1): 1.2
Evaporation Rate (Butyl Acetate=1): Less than 1

INGREDIENTS	CAS Reg. No.	Approx. Proportion	WES - TWA
Chlorinated Polymer	Not known	Med 10-60%	None Established #
Titanium Dioxide*	13463-67-7	Med 10-60%	10 mg/m ³ +
Aromatic Hydrocarbon	Not known	Med 10-60%	100ppm +
Barium Sulphate	7727-43-7	Low 0-10%	10 mg/m ³ +
Chlorinated Paraffin	108171-26-2	Low 0-10%	Possible Carcinogen **
Organo Clay	Not known	Low 0-10%	None Established +
Coloured Pigment	Mixture *	Low 0-10%	None Established +

* Proportions/Type vary with colour
+ NZ OSH (WES) 2002 **OSHA NTP 1994 # MANUFACTURERS DATA

HEALTH HAZARD INFORMATION

Health Effects:-

Skin: Moderately irritating to skin.

Eyes: Severely irritating to eyes.

Inhaled: Respiratory irritation, dizziness, nausea, loss of consciousness.

Swallowed: Can be harmful or fatal if swallowed. Can cause lung, kidney or liver damage.

Long Term Hazard: Repeated and prolonged occupational overexposure to solvents can damage liver, brain, and central nervous system.

First Aid:-

Skin: Wash affected area thoroughly with soap and water.

Eyes: Flush eyes immediately with plenty of water for at least 15 minutes and get medical attention.

Inhaled: Provide fresh air; give oxygen or artificial respiration if breathing laboured.

Swallowed: If swallowed dilute by giving two glasses of water to drink. DO NOT induce vomiting. Consult Physician or New Zealand National Poisons Centre (Ph 0800 764 766) Australian National Poisons Centre (Ph 1800 131 126) IMMEDIATELY. Never give anything by mouth to an unconscious person.

Advice to Doctor: Treat symptomatically.

PRECAUTIONS FOR USE

Personal Protection:-

Skin: Protective clothing. Gloves of neoprene or nitrile rubber -Industrial weight lined gauntlet recommended

Eyes: Solvent resistant safety eyewear with splash guards or side shields to prevent eye contact

Breathing: Class AUS 1 half face respirator with type A organic vapour filter and class P1 particulate filter.

Other: Use in well ventilated area with explosion proof equipment.

Ventilation: Sufficient ventilation, in volume and pattern, should be provided to keep air contaminant concentrations below WES - TWA limits.

SAFE HANDLING INFORMATION

Storage and Transport:-

Storage Maximum: 40°C. Store cool at constant temperature.

Temperature: Minimum: 1°C

Container Type and Material: Steel tins

Incompatible Substances: Strong oxidizers, acids, alkalis.

Conditions to Avoid: Heat, open flame, arc or sparks.

Hazardous Polymerisation: Will not occur.

Usual Decomposition Products Chlorinated Rubber resin chars and decomposes above 125°C releasing HCl and CCl₄

Spills: Keep spectators away and avoid breathing vapours or dust. Floor may be slippery: use care to avoid falling. Dike and contain spill with inert materials (eg sand). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Disposal: Incinerate the liquid and contaminated diking material at a permitted facility, or otherwise dispose of in accordance with all applicable regulations.

Fire/Explosion Hazard: Flash Point: >42°C

Auto Ignition Temperature: Not known

Upper Explosion Limit %: Not known

Lower Explosion Limit %: Not known

Extinguishing Media: Foam, Carbon Dioxide, Dry Chemical.

Special Fire Fighting Procedures:

Wear self contained breathing apparatus. Closed container may explode when exposed to extreme heat. Isolate from heat, electrical equipment, sparks and open flame. At temperatures above 125°C there is a tendency toward chemical decomposition with the evolution of Hydrochloric Acid.

Other Information:

Keep container closed, upright when not in use. Store in cool, dry, well ventilated area.

Contact Point: New Zealand Telephone 0800 737363 Australia Telephone 1800 738383 (24 hour)

It is Company Policy to maintain the most accurate and up to date information possible, and Resene Paints Limited aims to review these Data regularly. The information contained herein is based on data considered accurate and reliable to the best of our knowledge as of the date issued and subsequently made available from Resene Paints Limited. However, no warranty is expressed or implied regarding the accuracy of these Data or the results to be obtained from the use hereof. Persons using these Data are urged by Resene Paints Limited to satisfy themselves that these Data are the latest available from Resene Paints Limited and remain current and suitable for particular applications after intervening periods of time. Resene Paints Limited assumes no responsibility for personal injury or property damage to vendees, users, or third parties caused by the material. Such users or vendees assume all risks associated with the use of the material.