

## Resene Paints Limited

32-50 Vogel Street  
Naenae  
Wellington  
P O Box 38242  
Wellington Mail Centre

NEW ZEALAND

Telephone: (64) (4) 577 0500

Fax: (64) (4) 577 0600

e-mail: advice@resene.co.nz

Emergency Phone: NZ 0800 737363

Emergency Phone: Aust. 1800 738383

# MATERIAL SAFETY DATA SHEET

Version Number: 4

Date Issued: 1/07/2006

## IDENTIFICATION

Product Name: ARMOURCOTE 608

Other Names:

Proper Shipping Name PAINT RELATED MATERIAL

Uses: alkyd paint for steel

Group Standard Surface Coatings & Colourants. Flammable

Substance Classification 3.1B,6.1E,6.3A,6.4A,6.8B,6.9B,9.1C

U N Number: 1263

Classification of Hazardous Nature:

Dangerous Goods Class: 3

HAZARDOUS according to NZ HSNO Regulations. Regulated under NZS5433 for land transportation.

Hazchem Code: 3[Y]E

Packing Code: II

## Physical Description/Properties

Appearance-Viscosity-Odour-pH: Coloured liquid with hydrocarbon odour

Melting or Freezing Point: Not Known

Boiling Point: 110°C

Vapour Pressure (mm Hg @ 25 C): 1.25

Vapour Density (Air=1): 3.4 (heavier than air)

Solubility in Water (g/L @20 C): Insoluble

Percent Volatile (by weight): 50%

Specific Gravity (Water=1): 0.95-1.25

Evaporation Rate (Butyl Acetate=1): 1.2 (Faster than Butyl acetate)

## INGREDIENTS

### CAS Reg. No.

### Approx. Proportion

### WES - TWA

Xylene

1330-20-7

Med 10-60%

217 mg/m<sup>3</sup>

Toluene

108-88-3

Low 0-10%

188 mg/m<sup>3</sup>

+ NZ OSH (WES) 2002

## HEALTH HAZARD INFORMATION

### Health Effects:-

**Skin:** Causes irritation to skin upon repeated or prolonged contact.

**Eyes:** Causes irritation to eyes.

**Inhaled:** Excessive inhalation can cause headache, nausea, dizziness, asphyxiation.

**Swallowed:** Can be harmful if swallowed.

**Long Term Hazard:** Contains components that are known reproductive toxins and target organ toxins.

### First Aid:-

**Skin:** Remove / take off all contaminated clothing and wash before reuse. Wash skin with water/shower and plenty of soap. If skin irritation occurs get medical advice/attention.

**Eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists, get medical attention/advice.

Product Name: **ARMOURCOTE 608**

Page 1 of 2

**Inhaled:** Remove to fresh air and keep at rest in a position comfortable for breathing.

**Swallowed:** If swallowed dilute by giving two glasses of water to drink. DO NOT induce vomiting. Consult Physician or New Zealand National Poisons Centre (Ph 0800 764 766) Australian National Poisons Centre (Ph 1800 131 126) IMMEDIATELY. Never give anything by mouth to an unconscious person.

**Advice to Doctor:** Treat symptomatically.

---

### PRECAUTIONS FOR USE

**Personal Protection:-**

**Skin:** Protective clothing. Gloves of neoprene or nitrile rubber-Industrial weight lined gauntlet recommended

**Eyes:** Safety eyewear with splash guards or side shields to prevent eye contact complying with AS/NZS 1337:1992

**Breathing:** SPRAY: Half facepiece, class P1 particulate filter.

**Other:**

**Ventilation:** Sufficient ventilation, in volume and pattern, should be provided to keep air contaminant concentrations below WES - TWA limits.

---

### SAFE HANDLING INFORMATION

**Storage and Transport:-**

Storage Maximum: 40°C Store cool at constant temperature.

Temperature: Minimum: 1°C

**Container Type and Material:** Lacquer lined steel tins or polypropylene pails.

**Incompatible Substances:** Strong oxidizers, acids, alkalis

**Conditions to Avoid:** Freezing, excessive heat and changes in temperature.

**Hazardous Polymerisation:** Will not occur.

**Usual Decomposition Products** Oxides of Carbon and Hydrogen

**Spills:** Keep spectators away and avoid breathing vapours or dust. Floor may be slippery: use care to avoid falling. Dike and contain spill with inert materials (eg sand). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

**Disposal:** Incinerate the liquid and contaminated diking material at a permitted facility, or otherwise dispose of in accordance with all applicable regulations. Keep container closed, upright when not in use. Store in cool, dry, well ventilated area.

**Fire/Explosion Hazard:** Flash Point: 4°C

Auto Ignition Temperature: 495°C

Upper Explosion Limit %: 7.3

Lower Explosion Limit %: 1.2

**Extinguishing Media:** Foam, Carbon Dioxide, Dry Chemical.

**Special Fire Fighting Procedures:**

Materials can splatter above 100°C. Polymer film can burn.

**Other Information:**

**Approved Handl** Required when quantities in excess of 250Lt in container of 5Lt or less capacity or 500Lt in containers of greater than 5Lt capacity are handled.

**Contact Point: New Zealand Telephone 0800 737363 Australia Telephone 1800 738383 (24 hour)**

It is Company Policy to maintain the most accurate and up to date information possible, and Resene Paints Limited aims to review these Data regularly. The information contained herein is based on data considered accurate and reliable to the best of our knowledge as of the date issued and subsequently made available from Resene Paints Limited. However, no warranty is expressed or implied regarding the accuracy of these Data or the results to be obtained from the use hereof. Persons using these Data are urged by Resene Paints Limited to satisfy themselves that these Data are the latest available from Resene Paints Limited and remain current and suitable for particular applications after intervening periods of time. Resene Paints Limited assumes no responsibility for personal injury or property damage to vendees, users, or third parties caused by the material. Such users or vendees assume all risks associated with the use of the material.