

Resene Paints Limited

32-50 Vogel Street
Naenae
Wellington
P O Box 38242
Wellington Mail Centre
NEW ZEALAND

Telephone: (64) (4) 577 0500
Fax: (64) (4) 577 0600
e-mail: advice@resene.co.nz
Emergency Phone: NZ 0800 737363
Emergency Phone: Aust. 1800 738383

MATERIAL SAFETY DATA SHEET

Version Number: 1
Date Issued: 19/10/2007

IDENTIFICATION

Product Name: INTERIOR PAINTWORK CLEANER RTU

Other Names:

Proper Shipping Name PAINT RELATED MATERIAL

TOXIC SU

Uses: Paint work cleaner

Group Standard Non hazardous

Substance Classification

Classification of Hazardous Nature:

U N Number: Not regulated

NON HAZARDOUS according to NZ HSNO Regulations. Not Regulated under NZS5433 for land transportation

Dangerous Goods Class: Not regulated

Hazchem Code: Not regulated

Packing Code: Not regulated

Physical Description/Properties

Appearance-Viscosity-Odour-pH: Clear liquid, ammoniacal odour

Melting or Freezing Point:

Boiling Point: 100°C

Vapour Pressure (kPa @ 25° C): 2.33

Vapour Density (Air=1): Greater Than 1

Solubility in Water (g/L @20 C): Soluble

Percent Volatile (by weight): 100

Specific Gravity (Water=1): 1.00

Evaporation Rate (Butyl Acetate=1): Slow

INGREDIENTS

CAS Reg. No.

Approx. Proportion

WES - TWA

Water

7732-18-5

High 60-100%

Not applicable

Proprietary Ingredients

Various

Low 0-10%

Not known

+ NZ OSH (WES) 2002

HEALTH HAZARD INFORMATION

Health Effects:-

Skin:

Eyes:

Inhaled:

Swallowed:

Long Term Hazard:

First Aid:-

Skin: If skin irritation occurs get medical advice/attention.

Eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical attention/advice.

Product Name: **INTERIOR PAINTWORK CLEANER RTU**

Inhaled: Provide fresh air, give oxygen or artificial respiration if breathing laboured.

Swallowed: If swallowed dilute by giving two glasses of water to drink. DO NOT induce vomiting. Consult physician or New Zealand National Poisons Centre (Ph 0800 764 766) Australian National Poisons Centre (Ph 1800 131 126) IMMEDIATELY.

Advice to Doctor: Treat symptomatically.

PRECAUTIONS FOR USE

Personal Protection:-

Skin: Protective clothing. Gloves of neoprene or nitrile rubber

Eyes: Splashproof goggles

Breathing:

Other: Use in well ventilated area

Ventilation: Sufficient ventilation, in volume and pattern, should be provided to keep air contaminant concentrations below WES - TWA limits

SAFE HANDLING INFORMATION

Storage and Transport:-

Storage Maximum: 40°C Store cool at constant temperature

Temperature: Minimum: 1°C

Container Type and Material: Steel tins

Incompatible Substances: Strong oxidizers, acids, alkalis

Conditions to Avoid: Freezing, excessive heat and changes in temperature

Hazardous Polymerisation: Will not occur.

Usual Decomposition Products Oxides of Carbon

Spills: Keep spectators away and avoid breathing vapours or dust. Floor may be slippery: use care to avoid falling. Dike and contain spill with inert materials (eg sand). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Disposal: Incinerate the liquid and contaminated diking material at a permitted facility, or otherwise dispose of in accordance with all applicable regulations. Keep container closed, upright when not in use. Store in cool, dry, well ventilated area

Fire/Explosion Hazard: Flash Point: Not applicable

Auto Ignition Temperature: Not applicable

Upper Explosion Limit %: Not applicable

Lower Explosion Limit %: Not applicable

Extinguishing Media: Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Wear self contained breathing apparatus. Closed container may explode when exposed to extreme heat. Isolate from heat, electrical equipment, sparks and open flame.

Other Information:

Keep container closed, upright when not in use. Store in cool, dry, well ventilated area.

Approved Handl Not required

Contact Point: New Zealand Telephone 0800 737363 Australia Telephone 1800 738383 (24 hour)

It is Company Policy to maintain the most accurate and up to date information possible, and Resene Paints Limited aims to review these Data regularly. The information contained herein is based on data considered accurate and reliable to the best of our knowledge as of the date issued and subsequently made available from Resene Paints Limited. However, no warranty is expressed or implied regarding the accuracy of these Data or the results to be obtained from the use hereof. Persons using these Data are urged by Resene Paints Limited to satisfy themselves that these Data are the latest available from Resene Paints Limited and remain current and suitable for particular applications after intervening periods of time. Resene Paints Limited assumes no responsibility for personal injury or property damage to vendees, users, or third parties caused by the material. Such users or vendees assume all risks associated with the use of the material.