

Woodsman Wood Oil Stain

exterior



WARNING

KEEP OUT OF REACH OF CHILDREN



**TINT
BASE**

net contents

10 litres

tinters included

LL22410B 7/11

WARNING

Read label before use. Keep out of reach of children. Causes skin irritation. Causes eye irritation. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONS

DO NOT BREATHE FUMES/MISTS/SPRAYS/VAPOURS. USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Do not handle until all safety precautions have been read and understood. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Ground/bond container and receiving equipment as product is volatile and may generate a hazardous atmosphere. Take precautionary measures against static discharge. Use explosion proof electrical/ventilating/lighting and other equipment. Use only non-sparking tools. Avoid exposure - obtain special instructions before use. Wear protective gloves and eye/face protection and any other personal protective equipment as required. Contaminated work clothing should not be allowed out of the workplace. Wash thoroughly after handling. Do not contaminate any water supply. Collect spillage. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Avoid release into the environment.

FIRST AID

SWALLOWED: If ingested give water to dilute. Do not cause vomiting. Get medical attention without delay.

IF ON SKIN (or hair): Take off all contaminated clothing and wash before re-use. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: get medical attention/advice.

INHALATION: Move to fresh air. IF BREATHING DIFFICULT GET MEDICAL ATTENTION IMMEDIATELY.

Seek medical advice/attention if you feel unwell. If medical attention is required: have product container or label at hand. Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.
NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

CONTAINS: 2% Ammonium hydroxide.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D57.

If exposed or concerned get medical attention.

SPILLS: Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or mineral turps. Do not allow mineral turps to enter any drains. Refer to your local Council for disposal of dirty mineral turps.

FIRE: Use foam, carbon dioxide or dry chemical powder.

Resene Woodsman Wood Oil Stain is a solventborne wood oil stain matching the needs of timber with your desire to achieve the most natural appearance possible. Suitable for exterior timber including trafficable areas such as decks.

Preparation

- Treatment with Resene Timber and Deck Wash (see Data Sheet D813) is recommended for all substrates to remove dirt, natural stains and enhance the degree of product penetration. Ensure surfaces to be painted are dry, free from dust, dirt and loose material.

- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).

- Any bare timber surface that has been left exposed to the weather for more than one week should be thoroughly sanded.

- For repaints of existing penetrating stains remove any gross contamination and loose cellulose fibres.

- **All sanding dusts may be harmful and appropriate protection must be worn.** In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.

- Always colour test first to see your choice of Resene Woodsman Wood Oil Stain colour gives the result you want on the actual timber you are coating.

- Consult your Resene ColorShop or Reseller on coating severely weathered surfaces, exotic timbers, non-standard timbers and exterior doors and windows.

- Wood oil stains are not acceptable finishes for substrates that will be used in the collection of rainwater for drinking purposes. Only products that are expressly recommended for use in rainwater collection should be considered.

- This product may be used on a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Application

- Before use and regularly during use, stir well with a wide flat stirrer.
- Saturate the surface with Resene Woodsman Wood Oil Stain.
- All faces of the timber should be treated with special attention to end grains.

- Resene Woodsman Wood Oil Stain will not penetrate existing coatings or very hard latewood bands. Wipe excess Resene Woodsman Wood Oil Stain off with a dry, absorbent, lint free cloth rubbing along the grain.

- Contains powerful fungicides. Avoid skin contact and wear gloves when wiping off any excess.

- For new work apply the second coat after 24 hours and preferably before one week. Protection begins after full system is applied.

- Will not prevent checking of plywood.

- Will typically require maintenance after two summers. Performance is related to the depth of colour applied. Light applications, light colours and dressed surfaces may require maintenance sooner, while heavier applications, darker colours and rough sawn surfaces will require less maintenance.

- For new work apply the second coat after 24 hours and preferably before one week. Protection begins after full system is applied.

- Will not prevent checking of plywood.

- Will typically require maintenance after two summers. Performance is related to the depth of colour applied. Light applications, light colours and dressed surfaces may require maintenance sooner, while heavier applications, darker colours and rough sawn surfaces will require less maintenance.

Precautions

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d).

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



UN No. 1263 – Paint related product

FLAMMABLE LIQUID AND VAPOUR

Keep away from ignition sources such as heat/sparks/open flame/hot surfaces.

Keep closed when not in use.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited

7 Production Ave, PO Box 785, Ashmore City, Queensland, 4214

Phone 1800 738 383 Fax 1800 064 960

Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited

Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045

Phone (04) 577 0500 Fax (04) 577 0600

Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAJ, an accredited certification body. Printed on environmentally responsible paper that complies with EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Exterior timber surfaces.

Gloss level: None. Fully penetrating.

Typical coverage:

(a) Dressed timber: 1st coat, 10-12 square metres per litre; 2nd coat, 12-14 square metres per litre; apply a 3rd coat, 12-14 square metres per litre after 3-6 months.

(b) Rough sawn timber: 1st coat, 4-6 square metres per litre; 2nd coat, 9-11 square metres per litre.

(c) Badly weathered timber: 1st coat, 3-4 square metres per litre; 2nd coat 5-7 square metres per litre.

Dry time (minimum): 24 hours. Drying is slowed by low temperatures and high humidity.

Recoat time (minimum): 24 hours.

Primer required: No.

Usual number of coats: Two. Will require maintenance after two summers.

Application method: Brush, roller or spray.

Thinning: Do not thin.

Clean up: Mineral turps.

Colour range: Standard colours, refer Resene Exterior woodcare colour chart.

Before use: Stir well with a wide flat stirrer and also stir during application.

Enjoy the Resene Promise of Quality Guarantee on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 RESENE (NZ) or visit the Resene website.