

# Resene Roof and Metal Wash

liquid concentrate

Resene Roof and Metal Wash is the ideal pre-treatment for painted and unpainted galvanised steel and for general cleaning of any previously painted surface.

## exterior

### Typical uses

- New, painted, weathered galvanised steel
- Painted surfaces

	<b>Physical properties</b>
<b>Type</b>	Blended surfactants and cleansers
<b>Form</b>	Aqueous solution
<b>Solvent</b>	Water
<b>Solution viscosity</b>	Water thin
<b>Colour</b>	Colourless
<b>Dilution</b>	One part Resene Roof and Metal Wash to three parts freshwater
<b>VOC</b>	97 grams per litre Dipropylene Glycol Monomethyl Ether (see <a href="#">Resene VOC Summary</a> )

### Application

### Application and precautions

1. Provides an immediately cleaner surface.
2. Helps maintain the longevity of the paint finish.

### Precautions

1. Do not add Resene Roof and Metal Wash to paint.
2. Mild steel and aluminium are attacked by Resene Roof and Metal Wash and are unsuitable materials for either storage or application equipment.
3. Ensure product is well rinsed off glass surfaces. Concentrated product left on glass surfaces may etch the surface.

# Roof and Metal Wash

All information on this product is  
contained on the front of this Data Sheet.

This side has been intentionally left blank.

*Please ensure the current Data Sheet is consulted prior to specification or application of Resene products.  
If the surface you propose to coat is not referred to by this Data Sheet, please contact Resene for clarification.*

**In Australia**  
PO Box 924, Beenleigh, Qld 4207  
Call 1800 738 383, visit [www.resene.com.au](http://www.resene.com.au)  
or email [advice@resene.com.au](mailto:advice@resene.com.au)

**Resene**  
the paint the professionals use

**In New Zealand**  
PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Call 0800 RESENE (737 363), visit [www.resene.co.nz](http://www.resene.co.nz)  
or email [advice@resene.co.nz](mailto:advice@resene.co.nz)