

RESENE DECORATOR ALKYD UNDERCOAT

Resene Paints Ltd

Version No: 1.3

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: 03/02/2023

Print Date: 03/02/2023

L.GHS.NZLEN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	RESENE DECORATOR ALKYD UNDERCOAT
Synonyms	Not Available
Proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	10543
--------------------------	-------

Details of the manufacturer or supplier of the safety data sheet

Registered company name	Resene Paints Ltd
Address	32-50 Vogel Street Wellington New Zealand
Telephone	+64 4 577 0500
Fax	+64 4 5773327
Website	www.resene.co.nz
Email	advice@resene.co.nz

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7 days)	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	0800 764766	+64 800 700 112
Other emergency telephone numbers	Not Available	+61 3 9573 3188



Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification [1]	Flammable Liquids Category 3, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	3.1C, 6.1D (oral), 6.3A, 6.4A, 6.9B (narcotic effects), 9.1C

Label elements

Hazard pictogram(s)	 
Signal word	Warning

Hazard statement(s)

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

RESENE DECORATOR ALKYD UNDERCOAT

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only a well-ventilated area.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist/vapours/spray.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing, eye protection and face protection.

Precautionary statement(s) Response

P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P330	Rinse mouth.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Ingredients are required by the Hazard Substances (Safety Data Sheets) Notice 2017, EPA consolidation 30 April 2021 to be identified:

Mixtures

CAS No	%[weight]	Name
64742-82-1.	10-20	<u>naphtha petroleum, heavy, hydrodesulfurised</u>
64742-88-7	10-20	<u>solvent naphtha petroleum, medium aliphatic</u>
64742-48-9.	0.1-1	<u>naphtha petroleum, heavy, hydrotreated</u>
64742-95-6	1-10	<u>naphtha petroleum, light aromatic solvent</u>
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.

RESENE DECORATOR ALKYD UNDERCOAT

Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. ▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.
------------------	--

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures**Extinguishing media**

- ▶ Foam.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Advice for firefighters

Fire Fighting	▶ Alert Fire Brigade and tell them location and nature of hazard.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Liquid and vapour are flammable. Combustion products include: carbon monoxide (CO) carbon dioxide (CO ₂) other pyrolysis products typical of burning organic material.

SECTION 6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Remove all ignition sources. Contain spill with inert non-combustible absorbent then place in suitable, labelled container for waste disposal. Wipe up. Clean area with large quantity of water to complete clean-up.
Major Spills	Remove all ignition sources. Clear area of personnel and move upwind. Wear appropriate personnel protective equipment and clothing to prevent exposure. Avoid breathing in mists or vapours and skin or eyes contact. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible, contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authority.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage**Precautions for safe handling**

Safe handling	<ul style="list-style-type: none"> ▶ Containers, even those that have been emptied, may contain explosive vapours. ▶ Avoid unnecessary personal contact, including inhalation. ▶ DO NOT allow clothing wet with material to stay in contact with skin
Other information	▶ Store in original containers in approved flammable liquid storage area.

Conditions for safe storage, including any incompatibilities

Suitable container	▶ Packing as supplied by manufacturer.
Storage incompatibility	<ul style="list-style-type: none"> ▶ strong oxidisers ▶ attack some plastics, rubber and coatings ▶ may generate electrostatic charges on flow or agitation due to low conductivity.

SECTION 8 Exposure controls / personal protection**Control parameters**

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Continued...

RESENE DECORATOR ALKYD UNDERCOAT

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	naphtha petroleum, heavy, hydrodesulfurised	Stoddard solvent (White spirits)	100 ppm / 525 mg/m ³	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	solvent naphtha petroleum, medium aliphatic	Oil mist, mineral	5 mg/m ³	10 mg/m ³	Not Available	(om) - Sampled by a method that does not collect vapour
New Zealand Workplace Exposure Standards (WES)	naphtha petroleum, heavy, hydrotreated	Oil mist, mineral	5 mg/m ³	10 mg/m ³	Not Available	(om) - Sampled by a method that does not collect vapour

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
naphtha petroleum, heavy, hydrodesulfurised	300 mg/m ³	1,800 mg/m ³	29500** mg/m ³
solvent naphtha petroleum, medium aliphatic	1,200 mg/m ³	6,700 mg/m ³	40,000 mg/m ³
naphtha petroleum, heavy, hydrotreated	350 mg/m ³	1,800 mg/m ³	40,000 mg/m ³
naphtha petroleum, light aromatic solvent	1,200 mg/m ³	6,700 mg/m ³	40,000 mg/m ³

Ingredient	Original IDLH	Revised IDLH
naphtha petroleum, heavy, hydrodesulfurised	20,000 mg/m ³	Not Available
solvent naphtha petroleum, medium aliphatic	2,500 mg/m ³	Not Available
naphtha petroleum, heavy, hydrotreated	2,500 mg/m ³	Not Available
naphtha petroleum, light aromatic solvent	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
naphtha petroleum, light aromatic solvent	E	≤ 0.1 ppm

Notes:

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

MATERIAL DATA

IFRA Prohibited Fragrance Substance

The International Fragrance Association (IFRA) Standards form the basis for the globally accepted and recognized risk management system for the safe use of fragrance ingredients and are part of the IFRA Code of Practice.

WARNING: This substance is classified by the NOHSC as Category 2 Probable Human Carcinogen. These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits for benzene.

Odour Threshold Value: 34 ppm (detection), 97 ppm (recognition)

NOTE: Detector tubes for benzene, measuring in excess of 0.5 ppm, are commercially available.

For trimethyl benzene as mixed isomers (of unstated proportions)


Odour Threshold Value: 2.4 ppm (detection)

Use care in interpreting effects as a single isomer or other isomer mix.

Exposed individuals are **NOT** reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

NOTE P: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 0.01% w/w benzene (EINECS No 200-753-7).

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Personal protection	
Eye and face protection	▸ Safety glasses with side shields.
Skin protection	See Hand protection below
Hands/feet protection	▸ Wear chemical protective gloves, e.g. PVC. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.
Body protection	Overalls
Respiratory protection	Respiratory protection required in insufficiently ventilated working areas and during spraying. An approved respirator with a replaceable vapour/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to AS/NZS 1715 Standard, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716 Standard, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances. Recommended filter type: Type A filter (organic vapour).

RESENE DECORATOR ALKYD UNDERCOAT

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	White dispersion with mild solvent odour		
Physical state	Liquid	Relative density (Water = 1)	1.43-1.49
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	500-900
Initial boiling point and boiling range (°C)	130-150	Molecular weight (g/mol)	Not Available
Flash point (°C)	35-45	Taste	Not Available
Evaporation rate	Not Available BuAC = 1	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	26
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	385

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	<p>Inhalation of vapours may cause drowsiness and dizziness.</p> <p>High inhaled concentrations of mixed hydrocarbons may produce narcosis characterised by nausea, vomiting and lightheadedness. Central nervous system (CNS) depression may include nonspecific discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. A significant number of individuals exposed to mixed trimethylbenzenes complained of nervousness, tension, anxiety and asthmatic bronchitis. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression.</p>
Ingestion	<p>At sufficiently high doses the material may be hepatotoxic (i.e. poisonous to the liver).</p> <p>Ingestion of petroleum hydrocarbons may produce irritation of the pharynx, oesophagus, stomach and small intestine with oedema and mucosal ulceration resulting; symptoms include a burning sensation in the mouth and throat.</p>
Skin Contact	<p>Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period.</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.</p> <p>The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis.</p>

RESENE DECORATOR ALKYD UNDERCOAT

Eye	Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Petroleum hydrocarbons may produce pain after direct contact with the eyes.								
Chronic	Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. Serious damage (clear functional disturbance or morphological change which may have toxicological significance) is likely to be caused by repeated or prolonged exposure. Repeated or prolonged exposure to mixed hydrocarbons may produce narcosis with dizziness, weakness, irritability, concentration and/or memory loss, tremor in the fingers and tongue, vertigo, olfactory disorders, constriction of visual field, paraesthesias of the extremities, weight loss and anaemia and degenerative changes in the liver and kidney. On the basis, primarily, of animal experiments, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.								
RESENE DECORATOR ALKYD UNDERCOAT	<table border="1"> <thead> <tr> <th data-bbox="384 546 935 573">TOXICITY</th> <th data-bbox="935 546 1482 573">IRRITATION</th> </tr> </thead> <tbody> <tr> <td data-bbox="384 573 935 611">Not Available</td> <td data-bbox="935 573 1482 611">Not Available</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Not Available	Not Available				
TOXICITY	IRRITATION								
Not Available	Not Available								
naphtha petroleum, heavy, hydrodesulfurised	<table border="1"> <thead> <tr> <th data-bbox="384 651 871 678">TOXICITY</th> <th data-bbox="871 651 1482 678">IRRITATION</th> </tr> </thead> <tbody> <tr> <td data-bbox="384 678 871 716">Dermal (rabbit) LD50: >1900 mg/kg^[1]</td> <td data-bbox="871 678 1482 716">Eye: no adverse effect observed (not irritating)^[1]</td> </tr> <tr> <td data-bbox="384 716 871 754">Inhalation(Rat) LC50: >1.58 mg/L4h^[1]</td> <td data-bbox="871 716 1482 754">Skin: adverse effect observed (irritating)^[1]</td> </tr> <tr> <td data-bbox="384 754 871 792">Oral (Rat) LD50: >4500 mg/kg^[1]</td> <td data-bbox="871 754 1482 792">Skin: no adverse effect observed (not irritating)^[1]</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]	Inhalation(Rat) LC50: >1.58 mg/L4h ^[1]	Skin: adverse effect observed (irritating) ^[1]	Oral (Rat) LD50: >4500 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
TOXICITY	IRRITATION								
Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]								
Inhalation(Rat) LC50: >1.58 mg/L4h ^[1]	Skin: adverse effect observed (irritating) ^[1]								
Oral (Rat) LD50: >4500 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]								
solvent naphtha petroleum, medium aliphatic	<table border="1"> <thead> <tr> <th data-bbox="384 846 871 873">TOXICITY</th> <th data-bbox="871 846 1482 873">IRRITATION</th> </tr> </thead> <tbody> <tr> <td data-bbox="384 873 871 911">Dermal (rabbit) LD50: >2000 mg/kg^[2]</td> <td data-bbox="871 873 1482 911">Eye: no adverse effect observed (not irritating)^[1]</td> </tr> <tr> <td data-bbox="384 911 871 949">Inhalation(Rat) LC50: >4.3 mg/L4h^[1]</td> <td data-bbox="871 911 1482 949">Skin: no adverse effect observed (not irritating)^[1]</td> </tr> <tr> <td data-bbox="384 949 871 987">Oral (Rat) LD50: >5000 mg/kg^[2]</td> <td data-bbox="871 949 1482 987"></td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]	Inhalation(Rat) LC50: >4.3 mg/L4h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]	Oral (Rat) LD50: >5000 mg/kg ^[2]	
TOXICITY	IRRITATION								
Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]								
Inhalation(Rat) LC50: >4.3 mg/L4h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]								
Oral (Rat) LD50: >5000 mg/kg ^[2]									
naphtha petroleum, heavy, hydrotreated	<table border="1"> <thead> <tr> <th data-bbox="384 1041 871 1068">TOXICITY</th> <th data-bbox="871 1041 1482 1068">IRRITATION</th> </tr> </thead> <tbody> <tr> <td data-bbox="384 1068 871 1106">Dermal (rabbit) LD50: >1900 mg/kg^[1]</td> <td data-bbox="871 1068 1482 1106">Eye: no adverse effect observed (not irritating)^[1]</td> </tr> <tr> <td data-bbox="384 1106 871 1144">Inhalation(Rat) LC50: >4.42 mg/L4h^[1]</td> <td data-bbox="871 1106 1482 1144">Skin: adverse effect observed (irritating)^[1]</td> </tr> <tr> <td data-bbox="384 1144 871 1182">Oral (Rat) LD50: >4500 mg/kg^[1]</td> <td data-bbox="871 1144 1482 1182"></td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]	Inhalation(Rat) LC50: >4.42 mg/L4h ^[1]	Skin: adverse effect observed (irritating) ^[1]	Oral (Rat) LD50: >4500 mg/kg ^[1]	
TOXICITY	IRRITATION								
Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]								
Inhalation(Rat) LC50: >4.42 mg/L4h ^[1]	Skin: adverse effect observed (irritating) ^[1]								
Oral (Rat) LD50: >4500 mg/kg ^[1]									
naphtha petroleum, light aromatic solvent	<table border="1"> <thead> <tr> <th data-bbox="384 1236 871 1263">TOXICITY</th> <th data-bbox="871 1236 1482 1263">IRRITATION</th> </tr> </thead> <tbody> <tr> <td data-bbox="384 1263 871 1301">Dermal (rabbit) LD50: >1900 mg/kg^[1]</td> <td data-bbox="871 1263 1482 1301">Eye: no adverse effect observed (not irritating)^[1]</td> </tr> <tr> <td data-bbox="384 1301 871 1339">Inhalation(Rat) LC50: >4.42 mg/L4h^[1]</td> <td data-bbox="871 1301 1482 1339">Skin: adverse effect observed (irritating)^[1]</td> </tr> <tr> <td data-bbox="384 1339 871 1377">Oral (Rat) LD50: >4500 mg/kg^[1]</td> <td data-bbox="871 1339 1482 1377"></td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]	Inhalation(Rat) LC50: >4.42 mg/L4h ^[1]	Skin: adverse effect observed (irritating) ^[1]	Oral (Rat) LD50: >4500 mg/kg ^[1]	
TOXICITY	IRRITATION								
Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]								
Inhalation(Rat) LC50: >4.42 mg/L4h ^[1]	Skin: adverse effect observed (irritating) ^[1]								
Oral (Rat) LD50: >4500 mg/kg ^[1]									
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances								

RESENE DECORATOR ALKYD UNDERCOAT	Data demonstrate that during inhalation exposure,aromatic hydrocarbons undergo substantial partitioning into adipose tissues.
NAPHTHA PETROLEUM, HEAVY, HYDRODESULFURISED	No significant acute toxicological data identified in literature search.
SOLVENT NAPHTHA PETROLEUM, MEDIUM ALIPHATIC	The material may produce severe irritation to the eye causing pronounced inflammation. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). For toluene: Acute Toxicity Humans exposed to intermediate to high levels of toluene for short periods of time experience adverse central nervous system effects ranging from headaches to intoxication, convulsions, narcosis, and death.
NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT	* [Devoe] . Asthma-like symptoms may continue for months or even years after exposure to the material ends.
RESENE DECORATOR ALKYD UNDERCOAT & NAPHTHA PETROLEUM, HEAVY, HYDRODESULFURISED & SOLVENT NAPHTHA PETROLEUM, MEDIUM ALIPHATIC & NAPHTHA PETROLEUM, HEAVY, HYDROTREATED	Studies indicate that normal, branched and cyclic paraffins are absorbed from the mammalian gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length,with little absorption above C30.
RESENE DECORATOR ALKYD UNDERCOAT & NAPHTHA PETROLEUM, HEAVY, HYDRODESULFURISED &	For trimethylbenzenes: Absorption of 1,2,4-trimethylbenzene occurs after oral, inhalation, or dermal exposure.

RESENE DECORATOR ALKYD UNDERCOAT

NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT	
NAPHTHA PETROLEUM, HEAVY, HYDRODESULFURISED & NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT	For C9 aromatics (typically trimethylbenzenes - TMBs) Acute Toxicity Acute toxicity studies (oral, dermal and inhalation routes of exposure) have been conducted in rats using various solvent products containing predominantly mixed C9 aromatic hydrocarbons (CAS RN 64742-95-6).
NAPHTHA PETROLEUM, HEAVY, HYDRODESULFURISED & SOLVENT NAPHTHA PETROLEUM, MEDIUM ALIPHATIC & NAPHTHA PETROLEUM, HEAVY, HYDROTREATED	For petroleum: This product contains benzene, which can cause acute myeloid leukaemia, and n-hexane, which can be metabolized to compounds which are toxic to the nervous system.

Acute Toxicity	✓	Carcinogenicity	✗
Skin Irritation/Corrosion	✓	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

RESENE DECORATOR ALKYD UNDERCOAT	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available

naphtha petroleum, heavy, hydrodesulfurised	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	391mg/l	2
	EC50(ECx)	72h	Algae or other aquatic plants	391mg/l	2
	NOEC(ECx)	504h	Crustacea	0.097mg/l	2
	EC50	72h	Algae or other aquatic plants	0.53mg/l	2
	EC50	96h	Algae or other aquatic plants	0.58mg/l	2
	NOEC(ECx)	720h	Fish	0.02mg/l	2
	EC50	96h	Algae or other aquatic plants	0.277mg/l	2
	LC50	96h	Fish	0.14mg/l	2

solvent naphtha petroleum, medium aliphatic	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	48h	Crustacea	>100mg/l	1
	EC50	96h	Algae or other aquatic plants	450mg/l	1
	EC50	48h	Crustacea	>100mg/l	1

naphtha petroleum, heavy, hydrotreated	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	48h	Crustacea	>0.002mg/l	2
	EC50	96h	Algae or other aquatic plants	64mg/l	2
	EC50	48h	Crustacea	>0.002mg/l	2

naphtha petroleum, light aromatic solvent	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	72h	Algae or other aquatic plants	1mg/l	1
	EC50	72h	Algae or other aquatic plants	19mg/l	1
	EC50	96h	Algae or other aquatic plants	64mg/l	2
	EC50	48h	Crustacea	6.14mg/l	1

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark.

RESENE DECORATOR ALKYD UNDERCOAT

For 1,2,4 - Trimethylbenzene:

Half-life (hr) air: 0.48-16;

Half-life (hr) H2O surface water: 0.24 -672;

Half-life (hr) H2O ground: 336-1344;

Half-life (hr) soil: 168-672;

Henry's Pa m3 /mol: 385 -627;

Bioaccumulation: not significant.

For Aromatic Substances Series:

Environmental Fate: Large, molecularly complex polycyclic aromatic hydrocarbons, or PAHs, are persistent in the environment longer than smaller PAHs.

For petroleum distillates:

Environmental fate:

When petroleum substances are released into the environment, four major fate processes will take place: dissolution in water, volatilization, biodegradation and adsorption.

For C9 aromatics (typically trimethylbenzene - TMBs)

Chemicals in this category possess properties indicating a hazard for the environment (acute toxicity for fish, invertebrates, and algae from 1 to 10 mg/L).

For Xylenes:

log Koc : 2.05-3.08; Koc : 25.4-204; Half-life (hr) air : 0.24-42; Half-life (hr) H2O surface water : 24-672; Half-life (hr) H2O ground : 336-8640; Half-life (hr) soil : 52-672; Henry's Pa m3 /mol : 637-879; Henry's atm m3 /mol - 7.68E-03; BOD 5 if unstated - 1.4,1%; COD - 2.56,13% ThOD - 3.125 : BCF : 23; log BCF : 1.17-2.41.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	<p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory.</p> <ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ Recycle wherever possible. <p>Consult manufacturer for recycling option.</p> <p>Resene Paintwise accepts residual unwanted paint and packaging. See Resene website for Paintwise information. Or contact a Local Authority for the disposal information. Do not discharge the substance into the environment.</p>
------------------------------	---

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.

Do not allow product or wash water from cleaning or process equipment to enter drains or watercourses. It may be necessary to collect all wash water for treatment before disposal.

The generation of waste should be avoided or minimised wherever possible.

Disposal of this product should comply with Hazard Substances (Disposal) Notice 2017 (EPA Consolidation 30 April 2021) and local regulations.

Flammable substance can be disposed of if the substance is treated by using a method that changes the characteristics or composition of the substance so that the substance is no longer a hazardous substance, or exporting the substance from New Zealand as waste.


For treating and discharging processes contact your local authority.

The treating may include burning the substance if the burning is managed to ensure that no person, or place where a person may legally be present.

The substance may be discharged into the environment as waste or disposed into a landfill if the substance will not come into contact with oxidising substances and where is no ignition source which is capable to ignite the substance.

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	NO
HAZCHEM	*3Y

Land transport (UN)

UN number	1263
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

RESENE DECORATOR ALKYD UNDERCOAT

Transport hazard class(es)	Class	3
	Subrisk	Not Applicable
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions	163; 223; 367
	Limited quantity	5 L

Air transport (ICAO-IATA / DGR)

UN number	1263	
UN proper shipping name	Paint related material (including paint thinning or reducing compounds); Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)	
Transport hazard class(es)	ICAO/IATA Class	3
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	3L
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions	A3 A72 A192
	Cargo Only Packing Instructions	366
	Cargo Only Maximum Qty / Pack	220 L
	Passenger and Cargo Packing Instructions	355
	Passenger and Cargo Maximum Qty / Pack	60 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y344
	Passenger and Cargo Limited Maximum Qty / Pack	10 L

Sea transport (IMDG-Code / GGVSee)

UN number	1263	
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)	
Transport hazard class(es)	IMDG Class	3
	IMDG Subrisk	Not Applicable
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	EMS Number	F-E, S-E
	Special provisions	163 223 367 955
	Limited Quantities	5 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
naphtha petroleum, heavy, hydrodesulfurised	Not Available
solvent naphtha petroleum, medium aliphatic	Not Available
naphtha petroleum, heavy, hydrotreated	Not Available
naphtha petroleum, light aromatic solvent	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
naphtha petroleum, heavy, hydrodesulfurised	Not Available
solvent naphtha petroleum, medium aliphatic	Not Available
naphtha petroleum, heavy, hydrotreated	Not Available
naphtha petroleum, light aromatic solvent	Not Available

Continued...

RESENE DECORATOR ALKYD UNDERCOAT

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002662	Surface Coatings and Colourants Flammable Group Standard 2020

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

naphtha petroleum, heavy, hydrodesulfurised is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic	New Zealand Inventory of Chemicals (NZIoC)
New Zealand Approved Hazardous Substances with controls	New Zealand Workplace Exposure Standards (WES)

solvent naphtha petroleum, medium aliphatic is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List	New Zealand Approved Hazardous Substances with controls
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans	New Zealand Inventory of Chemicals (NZIoC)
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic	New Zealand Workplace Exposure Standards (WES)

naphtha petroleum, heavy, hydrotreated is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic	New Zealand Inventory of Chemicals (NZIoC)
New Zealand Approved Hazardous Substances with controls	New Zealand Workplace Exposure Standards (WES)

naphtha petroleum, light aromatic solvent is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic	New Zealand Inventory of Chemicals (NZIoC)
New Zealand Approved Hazardous Substances with controls	

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)
3.1C	500 L in containers more than 5 L	250 L
3.1C	1 500 L in containers up to and including 5 L	250 L

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
3.1C or 3.1D				10 L

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIIC / Australia Non-Industrial Use	Yes
New Zealand - NZIoC	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	03/02/2023
Initial Date	26/02/2018

SDS Version Summary

RESENE DECORATOR ALKYD UNDERCOAT

Version	Date of Update	Sections Updated
0.3	03/02/2023	Advice to Doctor, Chronic Health, Classification, Environmental, Physical Properties

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
PC—STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit.
IDLH: Immediately Dangerous to Life or Health Concentrations
ES: Exposure Standard
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index
AIIIC: Australian Inventory of Industrial Chemicals
DSL: Domestic Substances List
NDSL: Non-Domestic Substances List
IECSC: Inventory of Existing Chemical Substance in China
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
NLP: No-Longer Polymers
ENCS: Existing and New Chemical Substances Inventory
KECI: Korea Existing Chemicals Inventory
NZIoC: New Zealand Inventory of Chemicals
PICCS: Philippine Inventory of Chemicals and Chemical Substances
TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory
INSQ: Inventario Nacional de Sustancias Químicas
NCI: National Chemical Inventory
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.