RESENE WATERBORNE VINYL WALLPAPER SEALER

Resene Paints LTD

Version No: 3.4

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: **09/11/2023**Print Date: **09/11/2023**L.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier Product name RESENE WATERBORNE VINYL WALLPAPER SEALER Synonyms Not Available Other means of identification Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	11336

Details of the manufacturer or supplier of the safety data sheet

Registered company name	Resene Paints LTD
Address	32-50 Vogel Street Wellington 5011 New Zealand
Telephone	+64 4 5770500
Fax	+64 4 5773327
Website	www.resene.co.nz
Email	advice@resene.co.nz

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7days)	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	0800 764766	+64 800 700 112
Other emergency telephone numbers	Not Available	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification	of the	substance	or	mixture	

	• • • • • • • • • • • • • • • • • • • •
Classification [1]	Hazardous to the Aquatic Environment Long-Term Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	9.1C

Label elements

Hazard pictogram(s)	Not Applicable
Signal word	Not Applicable

Hazard statement(s

riazai u statement(s)	
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P273 Avoid release to the environment.

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Version No: **3.4** Page **2** of **7** Issue Date: **09/11/2023**

RESENE WATERBORNE VINYL WALLPAPER SEALER

Print Date: 09/11/2023

Substances

See section below for composition of Mixtures

Ingredients are required by the Hazard Substances (Safety Data Sheets) Notice 2017, EPA consolidation 30 April 2021 to be identified:

Mixtures

CAS No	%[weight]	Name
68131-40-8	0.1-1	alcohols C11-15 secondary ethoxylated
84133-50-6	0.1-1	alcohols C12-14 secondary ethoxylated
Legend:	Classified by Chemwatch; 2. Clas Classification drawn from C&L * L.	sification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; EU IOELVs available

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: • Wash out immediately with water. • If irritation continues, seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture Fire Incompatibility None known.

Advice for firefighters	
Fire Fighting	▶ Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	▶ Non combustible

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

IVIC	tillous and material for conta	minient and cleaning up
	Minor Spills	Control personal contact with the substance, by using personal protective equipment. Contain spill with sawdust, sand, earth, inert material or vermiculite then place in suitable, labelled container for waste disposal. Wipe up. Clean area with large quantity of water to complete clean-up.
	Major Spills	Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear appropriate personnel protective equipment and clothing to prevent exposure. Avoid breathing in mists or vapours and skin or eyes contact. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sawdust, sand, earth, inert material or vermiculite then place in suitable, labelled container for waste disposal. Wipe up. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Version No: 3.4 Page 3 of 7 Issue Date: 09/11/2023

RESENE WATERBORNE VINYL WALLPAPER SEALER

Print Date: 09/11/2023

Safe handling	Limit all unnecessary personal contact.
Other information	
Conditions for safe storage, inc	cluding any incompatibilities
Suitable container	As supplied by manufacturer.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
RESENE WATERBORNE VINYL WALLPAPER SEALER	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
alcohols C11-15 secondary ethoxylated	Not Available		Not Available	
alcohols C12-14 secondary ethoxylated	Not Available		Not Available	

Occupational Exposure Banding				
Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit		
alcohols C11-15 secondary ethoxylated	E	≤ 0.1 ppm		
alcohols C12-14 secondary ethoxylated	E ≤ 0.1 ppm			
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which correspond to protect worker health.			

MATERIAL DATA

 $\textbf{Exposed individuals are \textbf{NOT} reasonably expected to be warned, by smell, that the \textbf{Exposure Standard is being exceeded.} \\$

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a pazard or place a partier between the worker and the pazard	
Individual protection measures, such as personal protective equipment		
Eye and face protection	Safety glasses with side shields Chemical goggles.	
Skin protection	See Hand protection below	
Hands/feet protection	Wear general protective gloves, eg. light weight rubber gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.	
Body protection	Overalls	
Respiratory protection	No special measures required.	

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties		
Appearance	White acrylic dispersion	

Appearance	White acrylic dispersion		
Physical state	Liquid	Relative density (Water = 1)	1.27-1.31

Version No: **3.4** Page **4** of **7** Issue Date: **09/11/2023**

	RESENE WATERBORNE VINYL WALLPAPER SEALER			Print Date: 09/11/2023	
O	Odour Not A	Available	Partition coefficient n-octanol / water	Not Available	

Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Slight characteristic odour	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	8.2-9.0	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	980-1050
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available BuAC = 1	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	61-62
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	<1

SECTION 10 Stability and reactivity

Reactivity	See section 7	
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.	
Possibility of hazardous reactions	See section 7	
Conditions to avoid	See section 7	
Incompatible materials	See section 7	
Hazardous decomposition products	See section 5	

SECTION 11 Toxicological information

Information	on	toxicological	effects

miorimation on toxicological critical				
Inhaled	Inhaled The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models).			
Ingestion	The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'.			
Skin Contact The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using anima models).				
Еуе	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).			
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.			

RESENE WATERBORNE		
VINYL WALLPAPER SEALER		

TOXICITY

Not Available		Not Available
	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50: >=2000 mg/kg ^[1]	Skin (rabbit): 500 mg(open) mild

IRRITATION

Skin: no adverse effect observed (not irritating) $\ensuremath{^{[1]}}$

alcohols C12-14 secondary

alcohols C11-15 secondary

ethoxylated

ethoxylated

TOXICITY	IRRITATION
Not Available	Not Available

Version No: **3.4** Page **5** of **7** Issue Date: **09/11/2023**

RESENE WATERBORNE VINYL WALLPAPER SEALER

Print Date: 09/11/2023

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

ALCOHOLS C12-14 SECONDARY ETHOXYLATED

No significant acute toxicological data identified in literature search.

Polyethers, for example, ethoxylated surfactants and polyethylene glycols, are highly susceptible towards air oxidation as the ether oxygens will stabilize intermediary radicals involved.

Human beings have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps, detergents, and other cleaning products .

Alcohol ethoxylates are according to CESIO (2000) classified as Irritant or Harmful depending on the number of EO-units:

EO < 5 gives Irritant (Xi) with R38 (Irritating to skin) and R41 (Risk of serious damage to eyes)

EO > 5-15 gives Harmful (Xn) with R22 (Harmful if swallowed) - R38/41

ALCOHOLS C11-15 SECONDARY ETHOXYLATED & ALCOHOLS C12-14 SECONDARY ETHOXYLATED EO > 15-20 gives Harmful (Xn) with R22-41 >20 EO is not classified (CESIO 2000)

Oxo-AE, C13 EO10 and C13 EO15, are Irritating (Xi) with R36/38 (Irritating to eyes and skin) .

AE are not included in Annex 1 of the list of dangerous substances of the Council Directive 67/548/EEC

In general, alcohol ethoxylates (AE) are readily absorbed through the skin of guinea pigs and rats and through the gastrointestinal mucosa of rats

For high boiling ethylene glycol ethers (typically triethylene- and tetraethylene glycol ethers):

Skin absorption: Available skin absorption data for triethylene glycol ether (TGBE), triethylene glycol methyl ether (TGME), and triethylene glycol ether (TGEE) suggest that the rate of absorption in skin of these three glycol ethers is 22 to 34 micrograms/cm2/hr, with the methyl ether having the highest permeation constant and the butyl ether having the lowest.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

★ - Data either not available or does not fill the criteria for classification

— Data available to make classification

SECTION 12 Ecological information

Toxicity

Not Available	Not Available						
	1 22 22 22 22	Not Av	ailable	Not A	vailable	Not A	vailable
Endpoint	Test Duration (hr)		Species		Value		Source
LC50	96h Fish		Fish		3.2-7.2mg/l		4
NOEC(ECx)	672h		Crustacea		0.08mg/l		2
Endpoint	Test Duration (hr)	Specie	es	Value)	Sour	ce
Not Available	Not Available	Not Av	ailable	Not A	vailable	Not A	vailable
	LC50 NOEC(ECx) Endpoint Not Available	LC50 96h NOEC(ECx) 672h Endpoint Test Duration (hr) Not Available Not Available	LC50 96h NOEC(ECx) 672h Endpoint Test Duration (hr) Specie Not Available Not Available Not Av	LC50 96h Fish NOEC(ECx) 672h Crustacea Endpoint Test Duration (hr) Species Not Available Not Available Not Available	LC50 96h Fish NOEC(ECx) 672h Crustacea Endpoint Test Duration (hr) Species Value Not Available Not Available Not Available Not Available	LC50 96h Fish 3.2-7.2mg/l NOEC(ECx) 672h Crustacea 0.08mg/l Endpoint Test Duration (hr) Species Value Not Available Not Available Not Available Not Available	LC50 96h Fish 3.2-7.2mg/l NOEC(ECx) 672h Crustacea 0.08mg/l Endpoint Test Duration (hr) Species Value Sour

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 Disposal considerations

Version No: **3.4** Page **6** of **7** Issue Date: **09/11/2023**

RESENE WATERBORNE VINYL WALLPAPER SEALER

Print Date: 09/11/2023

Product / Packaging disposal

Legislation addressing waste disposal requirements may differ by country, state and/ or territory.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains
- Recycle wherever possible.

Consult manufacturer for recycling option.

Resene Paintwise accepts residual unwanted paint and packaging. See Resene website for Paintwise information. Or contact a Local Authority for the disposal information. Do not discharge the substance into the environment.

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.

Do not allow product or wash water from cleaning or process equipment to enter drains or watercourses. It may be necessary to collect all wash water for treatment before disposal. The generation of waste should be avoided or minimised wherever possible.

Disposal of this product should comply with Hazard Substances (Disposal) Notice 2017 (EPA Consolidation 30 April 2021).

For treating and discharging processes contact your local authority.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
alcohols C11-15 secondary ethoxylated	Not Available
alcohols C12-14 secondary ethoxylated	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
alcohols C11-15 secondary ethoxylated	Not Available
alcohols C12-14 secondary ethoxylated	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002670	Surface Coatings and Colourants Subsidiary Hazard Group Standard 2020

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

alcohols C11-15 secondary ethoxylated is found on the following regulatory lists

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

alcohols C12-14 secondary ethoxylated is found on the following regulatory lists

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 1 Quantity limits for dangerous goods

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 1 Quantity limits for dangerous goods

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

Certified Handler

Version No: 3.4 Page 7 of 7 Issue Date: 09/11/2023

RESENE WATERBORNE VINYL WALLPAPER SEALER

Print Date: 09/11/2023

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
New Zealand - NZIoC	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	09/11/2023
Initial Date	29/08/2016

SDS Version Summary

Version	Date of Update	Sections Updated
2.4	09/11/2023	Identification of the substance / mixture and of the company / undertaking - Synonyms, Identification of the substance / mixture and of the company / undertaking - Use, Name

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit.
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- ► PNEC: Predicted no-effect concentration
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.