N.B.

This chart is from the Resene historical file.

Please refer to current Resene colour charts for the latest colour options.

Resene lumber-sider

acrylic timber finish



The Paint the Professionals use



Resene lumber-sider acrylic timber finish

The stained look in a permanent finish.

Resene Lumber-sider is a new easy way of painting, producing a smooth natural satin appearance.

Available in 32 today colours and most British Standard colours.

Use on exterior and interior surfaces.

Pre-primed weatherboards. Timber fences. Sheds. Garden furniture.

Painted timber. Asbestos sidings. Concrete, brick and block work.



Lumber-sider is formulated on a 100% acrylic resin to ensure maximum durability over all exposure conditions.

Available in 32 today colours and most BSS colours, Lumber-sider can be used on almost all surfaces: new, old, painted or weathered. Weatherboards, natural timber, dressed or rough sawn fences, sheds, garden furniture. Fibrolite sheets and shadow

line. Concrete, brickwork, blockwork, galvanized iron. Lumber-sider should be applied in two coats. Dries in 20 minutes and can be recoated in 2 hours.

APPLICATION:

Normally applied by brush but can also be successfully sprayed or rolled.

Brushes and equipment wash out in water. Should not be applied at temperatures below 10°C (50°F).

Under hot conditions, it is preferable to work on the shaded side.

For porous surfaces thin with water.

On galvanized iron, preprime with one coat of esene Galvo-One Primer.

Lumber-sider covers 12 square metres per litre.

FOR ADDITIONAL COLOURS SEE THE RESENE BSS 101 AND BSS 88 COLOUR RANGES

Resene lumber-sider acrylic timber finish



MANUFACTURED BY STIPPLECOTE PRODUCTS LIMITED, GOUGH STREET, LOWER HUTT. PHONE 684-319
WELLINGTON, AUCKLAND, CHRISTCHURCH, DUNEDIN
NAPIER, HAMILTON