

Resene colour charts are updated regularly. This colour chart file is part of the colour chart archive, which we provide so you can view Resene colours that have been available over the years. Most older colours can still be tinted – check with your Resene ColorShop team if you need an older colour for your project.

To view the latest Resene colour charts, visit www.resene.com/colour-charts

Resene lumber-sider

acrylic timber finish



The Paint the Professionals use



DE PAULA



SPANISH WHITE



CHESTNUT



RAFAEL



CON CARN



SIERRA



BARLEY



MIGUEL



SPINACH



PLAZA



TOLEDO



AZTEC



BARK



BRACKEN



PANCHO



MIDNIGHT

Resene lumber-sider acrylic timber finish

The stained look in a permanent finish.

Resene Lumber-sider is a new easy way of painting, producing a smooth natural satin appearance.

Available in 32 today colours and most British Standard colours.

Use on exterior and interior surfaces.

Pre-primed weatherboards. Timber fences. Sheds. Garden furniture.

Painted timber. Asbestos sidings. Concrete, brick and block work.



TUMBLE-WEED



SOMBRERO



MADRID



KREON



UN-TORO



LONGHORN



NARANJA



MARQUEZ



ESPANA



MOSS



KAURI



SIDON



ROWAN



MANUKA



EL RANCHO



EL PASO

Lumber-sider is formulated on a 100% acrylic resin to ensure maximum durability over all exposure conditions.

Available in 32 today colours and most BSS colours, Lumber-sider can be used on almost all surfaces: new, old, painted or weathered. Weatherboards, natural timber, dressed or rough sawn fences, sheds, garden furniture. Fibrolite sheets and shadow

line. Concrete, brickwork, blockwork, galvanized iron. Lumber-sider should be applied in two coats. Dries in 20 minutes and can be re-coated in 2 hours.

APPLICATION:

Normally applied by brush but can also be successfully sprayed or rolled.

Brushes and equipment wash out in water. Should not be applied at temperatures below 10°C (50°F).

Under hot conditions, it is preferable to work on the shaded side.

For porous surfaces thin with water.

On galvanized iron, pre-prime with one coat of Resene Galvo-One Primer.

Lumber-sider covers 12 square metres per litre.



FOR ADDITIONAL COLOURS SEE THE RESENE BSS 101 AND BSS 88 COLOUR RANGES

Resene lumber-sider acrylic timber finish



MANUFACTURED BY STIPPLECOTE PRODUCTS LIMITED, GOUGH STREET, LOWER HUTT. PHONE 684-319
WELLINGTON, AUCKLAND, CHRISTCHURCH, DUNEDIN
NAPIER, HAMILTON