













he pots' drainage holes need to be large enough to fit the 10mm threaded rod, or drill a hole to size. Decorate or paint them before assembly.

## Step 1: Middle pot

Thread a nut, a spring washer and a flat washer onto the threaded rod. Screw the nut along about 35cm from the bottom end of the rod. Slide on a spring washer and then a flat washer. Next, slide on the middle pot up to the flat washer. To secure, slide on a flat washer under the pot and screw it up tight with another flange nut. Don't over-tighten and crack the pot.

## Step 2: Bottom pot

Add a flange nut, a spring washer and a flat washer to the bottom of the rod. Screw these along about 4-5cm, then slide on the bottom pot. Secure with another flat washer, then another

flange nut tightened up underneath the pot.

## Step 3: Top pot

From the top of the threaded rod, screw a flange nut down to where the bottom of the top pot will sit (I put mine down about 30-33cm). Add a flat washer, then the top pot. To secure, slide down another flat washer, then a spring washer, then a flange nut.

## Step 4: Eye bolt

From the top of the threaded rod, screw a flange nut down about 4cm, then a spring washer, then the eye nut.

Tighten the eye nut and the flange nut against one another to lock it in place.

To hang, install a screw-hook in a beam, pergola, eave, ceiling or under a balcony.

To watch the video, search for "vertical garden" on play.stuff.co.nz. ■



**JACOB LEAF** (Ngāpuhi) is *NZ Gardener's* DIY expert. When not constructing clever DIY projects for the magazine in his west Auckland garden, he works as a visual effects artist for film and TV.