

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

LL8431025 9-24



KEEP OUT OF REACH OF CHILDREN

# Resene

## Anti-Slip Grip Additive

### non-skid, slip-resistant finish

net contents 250 g

Add Resene Anti-Slip Grip Additive to pigmented or clear Resene flooring or foot trafficable coatings for wet slip resistance to meet the requirements of the NZ Building Code and AS 4586:2013. See the Resene website, [resene.com/anti-slip](http://resene.com/anti-slip) for substrates and application rates of tested systems.

#### Dose

- Add 250 g of Resene Anti-Slip Grip Additive per litre of paint. Lower dose rates will provide less slip resistance.
- Do not exceed the specified dose rate as this may have adverse effects on the product's characteristics. If in doubt, trial a small patch before painting the entire area.

Open to read instructions.

**SAFETY PRECAUTIONS** Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

**PRECAUTIONS** USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING. Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions.

#### **FIRST AID**

IF SWALLOWED: Rinse mouth.

IF ON SKIN (or hair): Rinse skin with plenty of water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

If medical advice is required have product container or label at hand.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

# Resene

the paint the professionals use

---

**In Australia:** PO Box 918, Ashmore City, QLD 4214

Ph 1800 738 383 Visit [resene.com.au](http://resene.com.au)

---

**In New Zealand:** PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045

Ph (04) 577 0500 Visit [resene.co.nz](http://resene.co.nz)

---

## Mixing

- Use a large mixing container, as the addition of Resene Anti-Slip Grip Additive will increase the total paint volume by approximately 20%.
- Add to the Resene paint, or for a two-pack product, add to the Base or add after the Base and Hardener have been thoroughly mixed and thinned.
- Mix thoroughly with a stirrer until perfectly homogeneous.

## Do not shake.

- Settling may occur upon standing. Stir regularly during application to ensure the mixture is uniform.

## Application

- Prep and prime the surface with the recommended substrate primer. Then apply the mixed product evenly by roller. Do not

apply below the temperature recommended for the topcoat.

- For exterior two coat systems, apply one coat of Resene Anti-Slip Grip Additive modified coating followed by a second coat of unmodified product.
- For interior three coat flooring systems, add Resene Anti-Slip Grit Additive to the second coat.
- Allow extra time before recoating due to the thicker film.

## Coverage

- The coverage of grit modified coating can be up to 50% less than unmodified product. Allow for this when estimating the quantity you will need.
- Resene Anti-Slip Grip Additive will alter the appearance of the finish providing a surface with a micro-texture.