

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.  
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

## net contents 800 mL

Must be mixed with the appropriate base. Makes 4 litres when mixed with 3.2 litres white or tinted Resene ArmourX IF 503 Base.

LL5470001H  
7-24

### SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes serious eye damage. May cause drowsiness or dizziness.

### PRECAUTIONS

DO NOT BREATHE MIST, VAPOURS OR SPRAY. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Use only outdoors or in a well-ventilated area. Wear protective gloves and clothing, eye and face protection. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid release to the environment.

### FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of water. If skin irritation occurs get medical advice. Take off immediately all contaminated clothing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTRE, doctor or first aider.

When seeking medical advice take this container with you.

Further information can be obtained from  
AUST: POISONS INFORMATION CENTRE 131 126  
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)  
or call Resene 0800 737 363.

CONTAINS: Gamma-Glycidoxypropyltrimethoxysilane 50-150 g/L,  
N-Butyl Acetate 300-500 g/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet RA81A.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with the recommended thinner. Do not allow thinner to enter any drains. Refer to your local Council for disposal of dirty thinner. See resene.com/cleanup for cleaning instructions.

**FIRE:** Blanket flames with dry chemical, carbon dioxide or foam. Closed containers may explode when exposed to extreme heat.

# DANGER

KEEP OUT OF REACH OF CHILDREN

# Resene

## ArmourX IF 500 Series

### HARDENER

Resene ArmourX IF 500 Series is a high performance two-pack finish for a wide variety of suitably prepared substrates. Available in pigmented and metallic colours, it's ideal when an isocyanate-free topcoat is required. Its quick dry properties allow early handling of coated items.

### General

- This product comprises a Base and Hardener, which must be mixed in the required ratio before application, preferably add the total contents of the Hardener container to the total contents of the Base container.
- Efficient mixing at all stages requires power mixing with an air or explosion proof mixer until uniformly blended.
- Mix each component separately before blending.
- Blend components together by stirring, until uniformly mixed and then allow to stand for the recommended induction time.
- After the induction period re-mix before application.
- Thinning requirements may vary according to application method, equipment and environmental conditions.
- If thinning is required add the recommended thinner after the components have been blended and thoroughly re-mix using the power mixer.
- Ensure the correct wet film thickness is applied to achieve the desired dry film thickness. Allow for any thinner added.
- Use of the incorrect thinner may have an adverse effect on application and performance.
- Drying is affected by low temperatures and high humidity.
- Use the mixed product within the stated pot life. The pot life of the mixed product is given for a specific temperature. Higher temperatures will reduce the pot life, conversely lower temperatures will increase it.
- The temperature of the substrate should be 3°C above the "Dew Point".
- The "Dew Point" requirement can be presumed to be satisfied if a thin clearly defined film of water applied to the cleaned surface with a damp cloth evaporates within 15 minutes.

- Following appropriate preparation, all surfaces must be dry and clean prior to painting.
- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, contact your local Resene ColorShop for your nearest Resene Technical Representative.

### Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.



ArmourX IF 500  
Series Hardener  
SDS

## Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 918, Ashmore City, Qld 4214  
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Limited  
Vogel St, PO Box 38242, Wgtn Mail Centre,  
Lower Hutt 5045  
Ph (04) 577 0500 Visit resene.co.nz

## Resene

Automotive & Light Industrial

Resene Automotive & Light Industrial  
PO Box 62282, Sylvia Park, Auckland 1644  
Call: 09 259 2738  
Visit resene.co.nz

## Quick check

**Name:** Resene ArmourX IF 500 Series acrylic epoxy gloss Hardener.

**Mixing ratio:** 4 parts Base, 1 part Hardener (by volume).

**Induction time:** 15-20 minutes.

**Pot life:** 8 hours at 20°C. Increased temperatures will shorten pot life.

**Dry time (minimum):** Touch dry: 60 minutes at 20°C (dependent upon film thickness). Drying is affected by low temperatures and high humidity.

**Recoat time (minimum):** 2 hours at 20°C.

**Thinner:** Resene Thinner No.6.

**Clean up:** Resene Thinner No.12.

**Limitations:** Must be applied over a two pack priming/undercoat system, including Resene ArmourX Adhesion Etch Primer (see Data Sheet RA31).

**Epoxies and polyaminoamides have been known to cause dermatitis. Take precautions to avoid skin contact.**

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

Read the appropriate Product Data Sheet and Safety Data Sheet before use.

## FLAMMABLE LIQUID AND VAPOUR

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.

## UN NO. 1263 – PAINT RELATED MATERIAL

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



9 418022 1101581