

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.  
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

**SAFETY PRECAUTIONS**

Read label before use. Keep out of reach of children. Harmful to aquatic life with long lasting effects.

**PRECAUTIONS**

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Avoid release to the environment.

**FIRST AID**

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so.

Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

When seeking medical advice take this container with you. Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a decorative/protective coating.

**SPILLS:** Wear appropriate clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

# Resene

fx

# blackboard paint

waterborne exterior/interior



Resene FX Blackboard Paint is a premium washable waterborne coating for interior and exterior smooth wallboards and panels where a hardwearing blackboard coating is required. Available in black or use Resene FX Chalkboard Paint for a range of Resene colours. Use with high quality blackboard chalk using a blackboard duster or soft cloth to remove chalk. If you wish to use Liquid Chalk, use Resene FX Write-on Wall Paint.

**Preparation**

• Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, oil (including mineral oil-based wood finishes or similar) and salt.

• Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).

• If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).

• **All sanding dusts can be harmful. Always wear appropriate protection. In particular, dust from old lead or chromate-based paints or old building materials containing asbestos can be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

• This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

**Priming**

• Apply Resene Quick Dry (see Data Sheet D45) as the first coat on fibre and particle boards.

• Seal plasterboard and stoppings with Resene Broadwall Waterborne Wallboard Sealer in dry areas (see Data Sheet D403). Seal fibrous plaster with Resene Sureseal.

• Seal hardboard with Resene Sureseal or Resene Waterborne Sureseal to promote the flow of the topcoats.

• Some 'soft' plasterboard preparatory products and under cured gypsum based stoppings may not be suitable basecoats for painting under stressed conditions. Reinforcement with a saturation coat of a fully penetrating primer (such as Resene Sureseal or Resene Waterborne

Smooth Surface Sealer) may be required. Use Resene Sureseal if the surface is water-stained.

• Prime all surfaces (except timber) which are highly absorbent, in poor condition, affected by efflorescence, friable, powdery or chalky with Resene Sureseal.

• New, sound cementitious and fibre cement substrates do not normally require a primer but priming with Resene Concrete Primer (see Data Sheet D405) is recommended to achieve the best long-term performance. Prime smooth/glossy cementitious, including GRC, with Resene ConcreteSeal 3 in 1 (see Data Sheet D409) to achieve topcoat adhesion.

• Repaints – spot prime all bare areas with the same primer shown for new work and proceed as for new work.

**Application**

• Prepare and prime the surface. Apply two topcoats of Resene FX Blackboard Paint by brush, roller or spray.

• Maintain good ventilation throughout the drying and curing period to ensure the paint is properly cured. Poor ventilation may inhibit curing and performance.

**Be PaintWise**

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.



Blackboard Paint  
SDS

Resene

the paint professionals use



Blackboard Paint  
TDS

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 918, Ashmore City, QLD 4214  
Ph 1800 738 383 Visit [resene.com.au](http://resene.com.au)

In New Zealand: Resene Paints Limited  
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045  
Ph (04) 577 0500 Visit [resene.co.nz](http://resene.co.nz)

**Quick check**

**Use on:** Interior and exterior smooth wallboards and panels where a hardwearing blackboard coating is required. Do not use on opening sashes and doors.

**Gloss level:** Low sheen – fully washable.

**Coverage:** 12 square metres per litre per coat.

**Dry time (minimum):** 30 minutes at 20°C. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

**Recoat time (minimum):** 3 hours at 20°C.

**Primer required:** Dependent on surface.

**Usual number of coats:** Two.

**Application method:** Brush, speed brush, roller or spray.

**Thinning:** In hot conditions thin with up to 5% Resene Hot Weather Additive to slow drying.

**Clean up:** Water.

**Colour range:** Black. For colours use Resene FX Chalkboard Paint. For other colour options, Resene SpaceCote Low Sheen can also be used as a blackboard finish.

**Before use:** Stir well with a wide flat stirrer.

**Enjoy the Resene Promise of quality** on premium paints. See your Resene ColorShop or the Resene website for a copy.

**Read the appropriate Data Sheet and Safety Data Sheet before application.**

**Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.**

