

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

PRECAUTIONS

Store in original labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Please recycle.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

If exposed or concerned get medical advice or attention.

When seeking medical advice take this container with you.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use in smoother finishes of Resene waterborne paints.

SPILLS

Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to run off into waterways. Refer to local waste management authority.

Resene

Brushing Additive

for a smoother finish on trim and joinery

net contents 250 mL



Resene Brushing Additive is specially formulated for addition to Resene waterborne enamels to reduce brush marking and produce a smoother finish on trim and joinery.

- Warm, dry conditions and hot surfaces can cause waterborne paints to dry too fast. This may lead to excessive foaming on application and generally poor application properties such as short wet edge times and impaired levelling.
- Resene Brushing Additive additions of 2%-5% will generally improve most application problems caused by too rapid drying. In more severe cases more Resene Brushing Additive is beneficial. Do not use more than 5% (200 mL per 4 litres). Do not use with Resene Hot Weather Additive.
- Higher levels of Resene Brushing Additive can reduce film build properties. This may show up as a tendency to run and sag and make it harder to achieve recommended spreading rates.

Recommended doses of Resene Brushing Additive

Amount of paint	Minimum	Maximum
500 mL	10 mL	25 mL
1 litre	20 mL	50 mL
2 litre	40 mL	100 mL
4 litre	80 mL	200 mL
10 litre	200 mL	500 mL

One capful = 10 mL.

Read the appropriate Safety Data Sheet before use.

Please ensure that use of this product is compatible with the paint. Resene does not accept any responsibility for the application of incorrect product to substrate. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Ltd
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Ltd
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz