

KEEP OUT OF REACH OF CHILDREN

Resene

Clearcoat UVS

waterborne U.V. protective glaze
exterior



9 418022 024477

LL28401B 4/14

WARNING

Read label before use. Keep out of reach of children. Harmful if swallowed. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT BREATHE FUMES/MISTS/SPRAYS/VAPOURS.
Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Wear protective gloves/protective clothing/eye and face protection. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

FIRST AID

IF SWALLOWED: Rinse mouth. Seek medical attention immediately. Further information available on the SDS.

IF INHALED: If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.

IF ON SKIN (or hair): Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.

IF IN EYES: If this product comes in contact with the eyes, wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. When seeking medical advice take this container with you.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

CONTAINS: UV Absorbers 10-15 gms/L, Fungicide < 10 gms/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D502.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Clearcoat UVS is based on a unique acrylic-urethane for ease of application and maximum life over painted surfaces. Formulated with U.V. absorbers, Resene Clearcoat UVS filters out harmful U.V. light, protecting the underlying coloured coat. Ideally suited for direct application to freshly painted bright organic hues and shades to aid colour retention by protecting these more vulnerable pigments against fading.

Preparation

- Ensure surfaces to be painted are in sound condition, dry, free from dirt, dust and loose material.
- Oil and grease must be removed using Resene Paint Prep and Housewash (see Data Sheet D812). If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Efflorescence on masonry must be treated (see Data Sheet D83).

• All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old asbestos containing building materials may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.

• This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, contact your local Resene ColorShop or Reseller.

Application

- To avoid foaming of material, do not shake and do not brush excessively. Stir well with a wide flat stirrer prior to application.
- Allow at least two hours between coats.
- Do not apply in direct sunlight.
- Do not apply over solventborne paint finishes.
- Not recommended for exterior tile or decorative aggregate flooring where ponding occurs.

Maintenance

(after a minimum of four weeks' drying)

See the Resene Caring for your paint finish brochure or the Resene website for full cleaning instructions.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Quick check

Use on: Exposed colours that may be prone to fading. Not for use on opening sashes and doors. Do not apply over solventborne paint finishes.

Gloss level: Gloss.
Coverage: 12 square metres per litre per coat. Coverage will vary dependent upon surface porosity and profile.

Dry time (minimum): 45 minutes at 18°C. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 2 hours.
Usual number of coats: 1.

Application method: Brush, roller (Resene No.10 Waterborne Clears sleeve) or airless spray.

Thinning and clean up: Water. In hot conditions may be thinned with up to 5% Resene Hot Weather Additive to slow drying.

Colour range: Clear.
Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.



Clearcoat SDS



Clearcoat TDS



the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using U.V. inks ensuring no emissions.