

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 1 litre
tint included

LL1911201 9-24

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection. Wash all exposed body areas thoroughly after handling. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

When seeking medical advice take this container with you. Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D50a.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways. See resene.com/cleanup for cleaning instructions.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

Colorwood natural wood stain

interior



9 418022 022879

REDUCING BASE/
TINT BASE

Resene Colorwood is an exciting way of treating natural timbers and enhancing the grain. It gives coloured timbers with the see-through look as it allows the natural grain of all timbers to show through.

Preparation

- Ensure the surface is free from oil, grease and glues.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).
- Stop all nail holes after staining with putty or a suitable filler matched to the required colour.
- Thoroughly sand surfaces prior to staining. Finish off with a fine sandpaper, remembering always to sand with the grain. Any marks left on the timber will show through Resene Colorwood.
- Ensure surfaces are completely dust free. Vacuum clean to remove dirt, dust and loose material.

All sanding dusts can be harmful. Always wear appropriate protection. Seek expert advice if working with lead, chromate or asbestos based materials or surfaces.

• The finished colour is influenced by the colour of the timber itself. Always colour test to see that your choice of Resene Colorwood stain gives the result you want on the actual timber you are staining.

• Bright or light colours give the best result over pale coloured woods. Dark timbers may show a darker colour than desired finish.

• This product may be used on a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

Application

- Before use and regularly during use stir well with a wide flat stirrer.
- Apply one full coat of Resene Colorwood ensuring there are no lap marks.
- Wipe off surplus immediately for the lightest stains, leave three minutes for pale shades or leave up to 5-15 minutes for a full strength colour.
- Avoid skin contact and wear gloves when wiping off

any surplus. Wipe excess Resene Colorwood off with a dry, absorbent, lint free cloth rubbing along the grain. Always wipe off surplus Resene Colorwood to ensure maximum adhesion of the topcoats.

- If the colour is too strong use Resene Colorwood Reducing Base to lighten the colour. Resene Colorwood Reducing Base may also be used on its own to enrich the colour of grain.
- Once dry, topcoat with Resene Aquaclear (see Data Sheet D59) or Resene Qristal ClearFloor (see Data Sheet D506 and D506A), Resene Qristal Clear polyurethane (see Data Sheet D52) or Resene Polythane (see Data Sheet D53).
- Hardwood and heart timbers may resist penetration of Resene Colorwood. It may be difficult to achieve strong colours on these timbers and the dry time will increase.
- Ensure enough stain of the same batch number is available to complete the job, as batch to batch colour variation can occur.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.



Colorwood SDS

Resene

the paint the professionals use



Colorwood TDS

In Australia: Resene Paints (Aust) Ltd
7 Production Ave, PO Box 918, Ashmore City, QLD, 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Ltd
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz

Quick check

Use on: Interior timber surfaces.

Gloss level: Low.

Coverage: 10-14 square metres per litre on dressed timber.

Dry time (minimum): 4 hours at 20°C. Drying is slowed by low temperatures and high humidity and is dependent on timber type, application rate and varnish.

Recoat time (minimum): 4 hours at 20°C for Resene Aquaclear and Resene Qristal ClearFloor, 24 hours at 20°C for Resene Qristal Clear polyurethane or 48 hours at 20°C for Resene Polythane.

Primer required: No.

Usual number of coats: One.

Application method: Brush or clean lint-free cloth.
Thinning and clean up: Water when wet, mineral turps when dry but uncured.

Colour range: Traditional and bright colours. See the Resene Interior wood stains colour chart.
Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy. Read the appropriate Product Data Sheet and Safety Data Sheet before use.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause standard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.