

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

Contractor

waterborne high build

exterior/interior

KEEP OUT OF REACH OF CHILDREN



9 418022 001607

WHITE

LL6130210F 5/24

net
contents
10 litres
tinter included

LL6130210B 5/24

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

PRECAUTIONS

DO NOT BREATHE THE MIST, VAPOURS OR SPRAY. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Remove or take off immediately all contaminated clothing and wash before reuse. Wash skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: get medical advice or attention.

When seeking medical advice take this container with you. Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383. NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a decorative/protective coating. For full technical instructions see Data Sheet D301.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Contractor uses advanced design polymers to achieve increased film build with standard application techniques. Skilled tradesperson-like application of the unthinned product will usually achieve complete hiding in one application. Based on wet-adhesion modified polymers for use over a wide variety of surfaces.

Preparation

- Ensure surfaces to be painted are in sound condition, dry, free from dirt, dust, loose material and salt.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Efflorescence on masonry **must be treated**.
- Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).
- Remove oil and grease with Resene Paint Prep and Housewash. Flush clean with water.
- Waterblasting is the best surface preparation prior to painting of weathered cementitious surfaces, galvanised steel and Zincalume.
- Fill cracks and holes in timber after priming.
- Prepare plasterboard to an appropriate level of finish. Apply Resene Broadwall Surface Prep & Seal (see Data Sheet D807), Resene Broadwall 3 in 1 (see Data Sheet D810) or Resene Sureseal (see Data Sheet D42 or waterborne see Data Sheet D42a) followed by lining paper in critical lighting areas.
- Round all sharp timber edges. Thoroughly sand or treat any bare timber surface that has been left exposed to the weather for more than one week with Resene TimberLock (see Data Sheet D48).
- **All sanding dusts can be harmful. Always wear appropriate protection. In particular, dust from old lead or chromate-based paints or old building materials containing asbestos can be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**
- Consult your Resene ColorShop or reseller for technical advice on painting of old cementitious roof tiles or if painting weathered galvanised steel and Zincalume or if corrosion is present.
- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small area first or contact your local Resene ColorShop or reseller.

Priming

- Resene TimberLock is recommended on Cedar and weathered exterior timber before priming.
- Resene Wood Primer (see Data Sheet D40) should be used on Cedar and other timbers that may stain.
- Resene Quick Dry (see Data Sheet D45) must be used as the first coat on Matai, Spotted Gum, Totara, and particle board.
- Prime/seal plasterboard and stoppings with Resene Broadwall Waterborne Wallboard Sealer in dry areas (see Data Sheet D403). Seal fibrous plaster with Resene Sureseal.
- Seal hardboard with Resene Sureseal or Resene Waterborne Sureseal to promote the flow of the topcoats.
- Some 'soft' plasterboard preparatory products and under cured gypsum based stoppings may not be suitable basecoats for painting under stressed conditions. Reinforcement with a saturation coat of a

fully penetrating primer (such as Resene Sureseal) may be required. Use Resene Sureseal if the surface is water stained.

- Prime all surfaces (except timber) which are in poor condition, affected by efflorescence, friable, powdery or chalky with Resene Sureseal.
- New timber - apply one coat of Resene Wood Primer or Resene Quick Dry.
- Do not allow galvanised steel or Zincalume to weather. If the galvanised steel or Zincalume has weathered use only Galvo One.
- New, sound cementitious and fibre cement substrates do not normally require a primer but priming with Resene Concrete Primer (see Data Sheet D405) is recommended to achieve the best long-term performance. Prime smooth/glossy cementitious, including GRC, with Resene ConcreteSeal 3 in 1 (see Data Sheet D409) to achieve topcoat adhesion. Spot prime nail heads (not galvanised) with Resene ArmourX Rust-Arrest (see Data Sheet RA30A). For galvanised nail heads use Resene ArmourX GP Metal Primer (see Data Sheet D411).
- Repaints - spot prime all bare areas with the same primer shown for new work and proceed as for new work.

Application

- Apply one full coat without thinning.
- Maintain good ventilation throughout the drying and curing period to ensure the paint is properly cured. Poor ventilation may inhibit curing and performance.

Maintenance (after a minimum of four weeks' drying)

See the Resene Caring for your paint finish brochure or the Resene website for full cleaning instructions.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.



Contractor SDS

Resene

the paint the professionals use



Contractor TDS

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz

Quick check

Use on: Exterior and interior cementitious surfaces and suitably primed timber, galvanised steel or Zincalume and wallboards.

Gloss level: Satin.

Coverage: 7 square metres per litre per coat.

Dry time (minimum): 3 hours. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period.

Recoat time (minimum): 3 hours. Drying is slowed by low temperatures and high humidity.

Primer required: Yes, dependent upon surface.

Usual number of coats: One. Blockwork may require two.

Application method: Brush, synthetic fibre roller, speed brush or spray.

Clean up: Water. Do not thin.

Colour range: White and pastels.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

Read the appropriate Data Sheet and Safety Data Sheet before application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.