

net contents 250 mL

LL1371025 1/22

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes serious eye irritation. Causes skin irritation.

PRECAUTIONS

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection.

FIRST AID

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

When seeking medical advice take this container with you.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a decorative/protective coating.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter or run into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene

FX Crackle

crackle effect

interior

WARNING

KEEP OUT OF REACH OF CHILDREN



Creating unique broken, antique looking finishes is quick and easy with Resene FX Crackle. Crackle finishes are best used on uneven or rough walls, furniture, picture frames, woodwork and small feature areas. Interior use only.

- Simply brush on one coat of your chosen tinted acrylic basecoat (such as Resene Lumbersider) at 10 sqm/L and allow to dry. Do not use a waterborne enamel as the basecoat or topcoat as Resene FX Crackle only works with standard acrylic finishes.

- Apply one coat of Resene FX Crackle and allow to dry (usually 30-40 minutes depending on temperature and humidity). Allow at least two hours before topcoating.

- Apply one coat of a Resene acrylic topcoat tinted to a contrasting colour to the basecoat. Resene FX Crackle will cause the topcoat to shrink and crack revealing the basecoat colour.

- If a clear overcoat is desired, use solventborne Resene Qristal Clear as a waterborne urethane may react with the effect.

- The crackle effect will vary depending on the application method, basecoat and topcoat used. Always try out a sample panel before starting the project.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld, 4207
Ph 1800 738 383 Visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO 9001 by Telarc SAI, an accredited certification body. Printed on paper produced in manufacturing facilities which comply with environmental management systems EMAS and ISO 14000. Printed using de-inkable toners for recycling with no solvent emissions. Please recycle.

