

**DANGER**

KEEP OUT OF REACH OF CHILDREN

# Resene

## Emulsifiable Solvent Cleaner oil and grease remover

net contents 4 litres

### Equipment

Stiff bristle scrubbing brush or broom, steam cleaning or waterblasting equipment. Safety glasses with side shields, protective clothing and gloves (neoprene or butyl rubber).

### Directions

Protect skin and eyes at all times with approved safety equipment.

1. Apply a heavy coat to all areas to be degreased.
2. Allow a contact time of 5-15 minutes, cleaning is aided by scrubbing surface, especially if surface is pitted.
3. Rinse surface by steamcleaning, waterblasting, or by hose and scrubbing.
4. If oil, grease or tar deposits remain, repeat the above procedure.
5. Allow degreased surface to dry thoroughly if painting.

### Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.

A-LL82604 7/14

### WARNING

Read label before use. Keep out of reach of children. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

### PRECAUTIONS

DO NOT BREATHE FUMES/MISTS/SPRAYS/VAPOURS. USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Ground/bond container and receiving equipment. Use explosion proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves, eye/face protection. Use other personal protective equipment as required. Wash thoroughly after handling. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Avoid release to the environment.

### FIRST AID

IF SWALLOWED: Rinse mouth. Immediately call a POISON CENTRE or doctor/physician.

IF ON SKIN (or hair): Remove/take off all contaminated clothing and wash before re-use. Wash skin with plenty of soap and water/shower. If skin irritation or rash occurs get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.

INHALATION: Remove to fresh air. IF BREATHING DIFFICULT GET MEDICAL ATTENTION IMMEDIATELY.

Call a POISON CENTRE or doctor/physician if you feel unwell. If medical attention is required: have product container or label at hand.

Further information can be obtained from  
AUST: POISONS INFORMATION CENTRE 131 126  
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)  
or call Resene 0800 737 363.

CONTAINS: Liquid Hydrocarbons 725 gms/L.

For removal of oil and grease from solvent resistant surfaces. For full technical instructions see Data Sheet D804.

**SPILLS:** Wear appropriate protective clothing. Eliminate all sources of ignition. Ventilate area, avoid breathing vapours. Use absorbent clean-up materials, such as fire retardant treated sawdust or diatomaceous earth to dike and contain spill. Scrape up and remove. Collect and seal in properly labelled drums. Refer to local waste management authority. Keep out of public sewers and waterways.

**CLEANING PAINT EQUIPMENT:** Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or mineral turps. Do not allow mineral turps to enter any drains. Refer to your local Council for disposal of dirty mineral turps.

**IN CASE OF FIRE:** Use foam, CO<sub>2</sub>, dry chemical for extinction.

For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



UN NO. 1263 – PAINT RELATED MATERIAL

**FLAMMABLE LIQUID AND VAPOUR**

Keep away from heat/sparks/open flames/  
hot surfaces. No smoking.



Emulsifiable Solvent Cleaner SDS

**Resene**

the paint the professionals use



Emulsifiable Solvent Cleaner TDS

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Phone 1800 738 383 Fax 1800 064 960  
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited  
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Phone (04) 577 0500 Fax (04) 577 0600  
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

