

net contents 500ml

A-LL1720050 5/17

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Harmful if swallowed. Harmful in contact with the skin. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs. Toxic to aquatic life with long lasting effects. Harmful to terrestrial vertebrates.

PRECAUTIONS

DO NOT BREATHE DUST, FUMES, GAS, MISTS, VAPOURS, SPRAYS. DO NOT EAT, DRINK OR SMOKE WHILE USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Wear protective gloves and clothing, eye and face protection. Use personal protective equipment as required. Ground or bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Avoid release to the environment. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Collect spillage.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor, physician or first aider if you feel unwell.

IF ON SKIN (or hair): Wash skin with plenty of soap and water. If skin irritation occurs get medical advice or attention. Take off contaminated clothing and wash before re-use.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

If exposed or concerned: Get medical advice or attention. When seeking medical advice take this container with you.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.
NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

CONTAINS: Zinc Phosphate 10-70 gms/L, Xylene 260-540 gms/L, Ethylbenzene 10-70 gms/L.

For use as a decorative/protective coating.

SPILLS: Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with the recommended thinner. Do not allow thinner to enter any drains. Refer to your local Council for disposal of dirty thinner.

IN CASE OF FIRE: Use foam, CO₂, dry chemical for extinction.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

**High Temp
Black Enamel**



BLACK

Resene High Temp Black Enamel is a flat, high heat coating formulated using heat resistant pigments in a silicone polymer resin that provides excellent colour retention and film integrity at working temperatures up to 538°C. This coating is designed for use on both ferrous and non-ferrous metal surfaces and is ideal to coat areas of wood stoves, flues, heaters, barbecues and other metal surfaces that are exposed to high temperatures. Do not use in areas with direct flame exposure. Resene High Temp Black Enamel gives good rust resistance when fully cured.

Surface preparation

- The surface to be painted must be clean, dry and free of oil, grease, mill scale and other contaminants; remove all rust. Cleaning methods include sandblasting, solvent scrub, wire brushing or vapour degreasing.
- Solvent clean repaired steel or bare steel with Xylene, Toluene or lacquer thinner. Use clean solvent and clean white wiping rags. Do not use coloured rags containing dye, which may dissolve in the solvent leaving incompatible contaminants on the surface.
- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**
- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Application

- Ensure that the area is well ventilated, that there are no open flames, and that appropriate protection is being worn.
- Mix well before use. No thinning is required for brush application.
- Allow to dry to a tack free state (30-45 mins at 15-25°C) before any heating is done. Cure at moderate heat (200-250°C for at least 1 hour) before subjecting the coating to high temperatures. Failure to do this may result in the coating cracking and losing adhesion.
- Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system when painting

in marginal painting conditions. Do not use gas or diesel burners to heat coated area as these produce water that will inhibit drying and curing. Poor ventilation may affect appearance and performance.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



UN NO. 1263 – PAINT RELATED MATERIAL

FLAMMABLE LIQUID AND VAPOUR

Keep away from heat, sparks, open flames and hot surfaces. No smoking.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAL, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Ferrous and non-ferrous metal surfaces, such as wood stoves, flues, heaters, barbecues and other metal surfaces that are exposed to high temperatures.

Gloss level: Flat.

Temperature resistance (dry): Continuous: 538°C; intermittent: 650°C.

Recommended dry film thickness (D.F.T.): 19-25 microns per coat.

Coverage: 19 square metres per litre per coat at 25 microns D.F.T.

Dry time: Allow to dry to a tack free state (30-45 minutes at 15-25°C). Cure for at least one hour at moderate heat (200-250°C) before subjecting the coating to high temperatures.

Application method: Brush or roller.

Colour: Black.

Usual number of coats: 1.

Thinning and clean up: Resene Thinner No.6.

When first subjected to heating there will be release of a solvent odour. Ensure when first heated that the area is well ventilated.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy. **In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.**

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.