

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 250ml

LL2753525 8-24

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation. May cause long lasting harmful effects to aquatic life.

PRECAUTIONS

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor, physician or first aider if you feel unwell.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If medical advice is required have product container or label at hand.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING APPLICATION EQUIPMENT:

Brush/roll out as much product as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways. See resene.com/cleanup for cleaning instructions.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Resene ProSelect Anti-Slip

timber flooring finish slip resistance additive

KEEP OUT OF REACH OF CHILDREN



Developed specifically for professional flooring contractors, Resene ProSelect Anti-Slip is an additive for the Resene ProSelect system providing wet slip resistance to meet the requirements of the NZ Building Code and AS 4586:2013.

FOR PROFESSIONAL USE ONLY

Important note: For all processes for hardwood timber floor coating from the initial consultation with the client, through to final application/finishing and maintenance follow the guidelines in the Australasian Timber Flooring Association (ATFA) Information Guide Manual and website, atfa.com.au.

Dose rate: 100 ml per litre of Base or 80 ml per litre of ready-to-use (premixed and thinned) of the final coat of the Resene ProSelect finish to achieve a P4 wet slip resistance rating. Lower dose rates will provide lower levels of slip resistance. Do not exceed the specified dose rate by more than 20%.

Mixing: Add to the Resene ProSelect Base or after the Base and Resene ProSelect Cure have been thoroughly mixed and thinned. Mechanical stir. Do not shake. Agitate the mixture periodically during application to ensure a uniform mixture is maintained. Spread evenly during application.

IMPORTANT NOTE/S: Use of this anti-slip additive will alter the appearance of the finish providing a surface with a smooth micro-texture. Do NOT add Resene ProSelect Anti-Slip to finishes containing Resene ProSelect Naturadd – replace Resene ProSelect Naturadd with Resene ProSelect Anti-Slip where slip resistance is required. Refer to the Resene ProSelect Gloss Level Chart to compare gloss levels with and without the Resene ProSelect Anti-Slip additive.

Clean up: Water.

Be PaintWise: For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.

Refer to resene.com/proselect or the Resene ProSelect Technical Data Booklet for more detailed information.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

Read the appropriate Product Data Sheet and Safety Data Sheet before use.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Ltd
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Ltd
Vogel St, PO Box 38242, Wgtn Mall Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz