

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

# Resene

## ProSelect

## Stain Base

professional timber flooring finish

**WARNING**

KEEP OUT OF REACH OF CHILDREN



9 418022 069836

**CLEAR**

net  
contents  
4 litres

LL2758004F 10/17

**SAFETY PRECAUTIONS**

Read label before use. Keep out of reach of children. Causes serious eye irritation. Causes skin irritation.

**PRECAUTIONS**

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Wear protective gloves and clothing, eye and face protection. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods of cleaning equipment and disposing of unwanted paint.

**FIRST AID**

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or physician if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs, get medical advice or attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

If exposed or concerned get medical advice or attention.

If medical advice is required have product container or label at hand.

Further information can be obtained from  
AUST: POISONS INFORMATION CENTRE 131 126  
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)  
or call Resene 0800 737 363.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING APPLICATION EQUIPMENT:** Brush/roll out as much product as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Developed specifically for professional flooring contractors, Resene ProSelect Stain Base is a waterborne tint base designed to be coloured using the ProSelect Colour Concentrates.

**FOR PROFESSIONAL USE ONLY**

**Important note:** All processes for hardwood timber floor coating from the initial consultation, with the client, through to final application/finishing and maintenance should follow the guidelines set out in the Australasian Timber Flooring Association (ATFA) Information Guide Manual and Web Site, [www.atfa.com.au](http://www.atfa.com.au).

**Mixing and thinning:** Add Resene ProSelect Colour Concentrate to achieve desired colour strength. Up to 10% Resene ProSelect Colour Concentrate is typical (do not add more than 20% by volume). Shake or stir well until colour is even.

**IMPORTANT NOTE:** Dilute with an equal volume of water immediately BEFORE application and mix thoroughly.

**Application:** Suitable for application by various methods such as brush, wipe, rag and mop. Apply a thin even coat and for best results work into the timber following the grain. Remove any excess before it dries. Drying time is dependent upon application conditions and porosity of the timber. Do not flood the timber surface.

Mix regularly while applying to ensure a uniform colour is maintained. Thinned product must be used the same day it is mixed.

**Clean up:** Water.

Refer to [www.resene.com/proselect](http://www.resene.com/proselect) or the Resene ProSelect Technical Data Booklet for more detailed information.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.



Resene ProSelect  
info centre

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause standard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



# Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Phone 1800 738 383 Fax 1800 064 960  
Email [advice@resene.com.au](mailto:advice@resene.com.au) or visit [www.resene.com.au](http://www.resene.com.au)

In New Zealand: Resene Paints Limited  
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Phone (04) 577 0500 Fax (04) 577 0600  
Email [advice@resene.co.nz](mailto:advice@resene.co.nz) or visit [www.resene.co.nz](http://www.resene.co.nz)

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA1, an accredited certification body. Printed on environmentally responsible paper which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.