

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes mild skin irritation. Causes eye irritation. Harmful to aquatic life.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wash all exposed external body areas thoroughly after handling. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or physician if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of water. If skin irritation occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

If exposed or concerned get medical advice or attention. If medical advice is required have product container or label at hand.

Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D326.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

SmartTouch

Conductive Coating

interior waterborne wallpaint

turn your wall
into a light switch!



Turn your wall into a light switch with Resene SmartTouch. Resene SmartTouch conductive coating is designed to turn an area up to two square metres into an invisible switch using technology adapted from touch screens. Rather than fumbling for a light switch, a section of wall, column or almost any other area can become the switch. Simply double-tap to turn lights on and off or use other available Touch Commands for more complex lighting control.

Resene SmartTouch is a basecoat product and may be finished in your favourite Resene topcoat and colour or may be wallpapered over (smooth/low texture wallpapers only). This gives you an infinite range of decorating options. Once the painting or wallpaper is done, the wall looks just like a normal wall.

Ideal for new builds or existing homes and buildings. Use in areas such as high traffic entranceways, stairwells, bedrooms and living spaces. Easy to apply and suitable for use by DIY or professional painters. Use an electrician to connect Resene SmartTouch into mains lighting.

Full Resene SmartTouch system instructions are available from www.resene.com/smarttouch.

Preparation

- Ensure surfaces to be painted are in sound condition, thoroughly sanded to a smooth finish, dry, free from dirt, dust and loose material.
- Oil and grease must be removed using Resene Paint Prep and Housewash (see Data Sheet D812). If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Efflorescence on masonry **must be treated** (see Data Sheet D83).
- Where staining is present the source must be removed.
- Fill cracks and holes in interior walls before sealing.
- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

• This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Sealing

• Plasterboard must be prepared to an appropriate level of finish. Either Resene Broadwall Surface Prep & Seal (see Data Sheet D807), Resene Broadwall 3 in 1 (see Data Sheet D810) or Resene Sureseal (see Data Sheet D42) followed by lining paper is recommended in critical lighting areas.

Application

- Ensure you follow the Resene SmartTouch system instructions

before topcoating. DO NOT paint over the wire connection point unless Resene SmartTouch connection is already in place.

• Apply at least two coats allowing dry time between coats. For an invisible finish after topcoating, feather the edges during application or by light sanding after drying.

Topcoat

- Topcoat in your choice of Resene paint finish. Resene SpaceCote Low Sheen is recommended for most interior surfaces as it is durable and easy to wipe clean.
- Do not use with Resene Magnetic Magic or any paint, coating or wallpaper containing metal.
- Ensure you follow the Resene SmartTouch system instructions when determining the area to be coated and for connecting the paint to lighting using a switchplate or direct-to-surface mounting.
- Each Resene SmartTouch area should be less than two square metres in area. Larger areas will affect performance.

Connection

• Installation and maintenance of Resene SmartTouch electronics is only to be performed by a suitably qualified installer, in accordance with the appropriate local wiring and safety regulations.

Maintenance

(after a minimum of four weeks' drying)

The topcoated wall may be cleaned just like a normal painted wall. See the Resene Caring for your paint finish brochure or the Resene website for full cleaning instructions.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.

Resene

the paint the professionals use



Resene SmartTouch info centre

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Ph 1800 738 383 Visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAJ, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Smooth, non-textured interior areas where the ability to switch on lights is desired.

Colour range: Black.

Coverage: 14 square metres per litre per coat.

Dry time (minimum): 45 minutes. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 3 hours, overnight dry before topcoating.

Primer required: Dependent on surface.

Usual number of coats: 2-3 (depends on roller sleeve used).

Application method: Brush, Resene No.1 or No.4 roller sleeve or spray.

Thinning: Do not thin.

Clean up: Water.

Before use: Stir well with a wide flat stirrer.

Overcoat: With your chosen Resene paint finish. Resene SpaceCote Low Sheen or Resene Lustacryl (semi-gloss) are recommended for easy cleanability.

Full Resene SmartTouch system instructions are available from www.resene.com/smarttouch.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.