

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.

Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

DANGER

KEEP OUT OF REACH OF CHILDREN

Resene

Solventborne Aquapel water repellent exterior/interior

LL2790004 7-24

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes serious eye irritation. Causes mild skin irritation. May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child. May be fatal if swallowed and enters airways. Suspected of causing cancer. Toxic to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT BREATHE MIST, VAPOURS OR SPRAY. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Wear protective gloves and clothing, eye and face protection. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Immediately call a POISON CENTRE, doctor or first aider. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTRE, doctor or first aider.

When seeking medical advice take this container with you. If exposed or concerned: Call a POISON CENTRE.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

For use as a water repellent on most porous building materials.
For full technical instructions see Data Sheet D655.

CONTAINS: Isoparaffins Petroleum Hydrotreated >720 g/L.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority. Clean up spillage.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with the recommended thinner. Do not allow thinner to enter any drains. Refer to your local Council for disposal of dirty thinner. See resene.com/cleanup for cleaning instructions.

FIRE: Use foam, carbon dioxide or dry chemical powder.



SHAKE WELL BEFORE USE



CLEAR

Resene Solventborne Aquapel is a clear silicone water repellent for application on most porous building materials to impart watershedding properties.

Preparation

- Ensure the surface is in sound condition, dry and free from dirt, dust, loose material, oil (including mineral oil-based wood finishes or similar) and salt.
- Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Flush clean with water.
- Remove oil and grease using Resene Paint Prep and Housewash.
- **All sanding dusts can be harmful. Always wear appropriate protection. Seek expert advice if working with lead, chromate or asbestos based materials or surfaces.**
- This product may be used to treat a wide variety of surfaces. If the surface you propose to treat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller.

Application

- Resene Solventborne Aquapel can only be used

over a porous surface that will allow the treatment to penetrate. It cannot be applied over a fully sealed surface then overcoated.

- Stir thoroughly before use.
- Apply by brush, roller or low pressure spray.
- Saturate the surface with Resene Solventborne Aquapel.
- Remove any Resene Solventborne Aquapel that gets onto glass to avoid the risk of staining.
- If it starts to rain, immediately cease application and cover all treated areas that have yet to dry out.
- Maintain good ventilation throughout the drying and curing period to ensure the treatment is properly cured. Poor ventilation may inhibit curing and performance.
- Maximum hydrophobicity (or water repellence) develops after a few days weathering.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.



FLAMMABLE LIQUID AND VAPOUR

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



Resene
the paint the professionals use



In Australia: Resene Paints (Aust) Ltd
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Ltd
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz

Quick check

Use on: Most porous building materials.

Gloss level: None – fully penetrating.

Typical coverage: Dependent on surface porosity – typically 2.5 square metres per litre for concrete block, 8-10 square metres per litre for concrete (tilt, precast, plaster).

Dry time (minimum): Penetrates – up to 48 hours at 20°C for solvent to evaporate.

Recoat (minimum): 6 hours at 20°C.

Primer required: No.

Usual number of coats: 1-2 to achieve saturation.

Application method: Low pressure spray is best, brush or roller.

Thinning and clean up: Mineral turps.

Colour range: Clear.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

Read the appropriate Product Data Sheet and Safety Data Sheet before use.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.