

WARNING

Read label before use. Keep out of reach of children. May be harmful if swallowed. Causes serious eye irritation. May cause an allergic skin reaction. Causes skin irritation. May damage fertility or the unborn child. Harmful to aquatic life with long lasting effects. Harmful to terrestrial vertebrates.

PRECAUTIONS

AVOID BREATHING DUST/FUMES/GAS/MIST/VAPOURS/SPRAY. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Wear protective gloves/protective clothing, eye and face protection. Contaminated work clothing should not be allowed out of the workplace. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Avoid release to the environment. Obtain special instructions before use.

FIRST AID

IF SWALLOWED: Do NOT induce vomiting. Rinse mouth. Call a POISON CENTRE or doctor/physician if you feel unwell

IF ON SKIN (or hair): Remove/take off contaminated clothing and wash before re-use. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention/advice.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If exposed or concerned: Get medical advice/attention. Call a POISON CENTRE doctor/physician if you feel unwell.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

Contains: N-methyl-pyrrolidone 585-650 gms/L, Pine oil <10 gms/L.

For full technical instructions see Data Sheet D81.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or mineral turps. Do not allow mineral turps to enter any drains. Refer to your local Council for disposal of dirty mineral turps.

FIRE: In case of fire: Use foam, CO₂, dry chemical for extinction.

DANGER

KEEP OUT OF REACH OF CHILDREN

Resene**Strip-Off**
paint stripper

net contents 1 litre

Resene Strip-Off is an effective, low odour paint stripper, free from Methylene Chloride, Caustic Soda and other strong alkalis. Resene Strip-Off is non-drip and suitable for removing paint from common household items.

- Low hazard - Methylene Chloride free.
- Clean up in water and detergent.
- Can be applied on vertical surfaces.
- Penetrates deep into paint film.
- Strips a wide range of paints.
- Active for up to 4-6 hours.
- Non-drip formula.

Preparation

• Ensure surface is dry prior to application of Resene Strip-Off.

• Roughen old paint with coarse sandpaper to assist in the penetration of Resene Strip-Off.

• **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

Application

• Although Resene Strip-Off is a low odour material it is nevertheless a very powerful solvent; wear goggles and solvent resistant gloves.

• Apply a full flowing coat to the surface by brush to thoroughly wet the surface. Resene Strip-Off should then be left in this wet condition for not less than 30 minutes before testing. If the paint removes easily use a broadknife to scrape surface.

• If the paint is still adhering firmly, leave another 30 minutes before testing again. A softening period of up to, or even exceeding, one hour may be necessary.

• Do not allow Resene Strip-Off to dry on the surface.

• Scrubbing with a nylon pot scourer will assist in the stripping process.

• After stripping the surface to ensure complete removal of the residues, scrub down with weak detergent and water.

- Allow surface to dry for 24 hours and lightly sand.
- Brushes should be cleaned using detergent and water.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.

Quick check

Use on: Enamels, varnishes, acrylics, automotive paints and two pack products. Do not use on vinyl, rubber, plasterboard and fibreglass surfaces.

Coverage: 1-2 square metres per litre per coat.

Stripping time: 30 minutes to 2 hours depending on paint type.

Usual number of coats: One. A second application may be required to remove stubborn paint layers.

Application method: Brush.

Thinning: Do not thin.

Clean up: Wash surfaces with weak detergent and cold water to remove residue.

Colour: Pale amber.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that the colour in this container is the same as selected. Resene accepts no responsibility for the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

**Resene**

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242
Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

