

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May damage fertility or the unborn child.

PRECAUTIONS

DO NOT BREATHE THE MIST, VAPOURS OR SPRAY. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Use only outdoors or in a well-ventilated area. Wear protective gloves and clothing, eye and face protection. Wash all exposed external body areas thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Obtain special instructions before use.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell. IF ON SKIN (or hair): Wash with plenty of water. If skin irritation occurs get medical advice. Take off all contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If exposed or concerned get medical advice or attention. Call a POISON CENTRE doctor/physician if you feel unwell.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

Contains: N-Methyl-2-Pyrrolidone 420-840 g/L.

For full technical instructions see Data Sheet D81.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or mineral turps. Do not allow mineral turps to enter any drains. Refer to your local Council for disposal of dirty mineral turps. See resene.com/cleanup for cleaning instructions.

FIRE: In case of fire: Use foam, CO₂, dry chemical for extinction.

DANGER
KEEP OUT OF REACH OF CHILDREN

Resene

Strip-Off paint stripper

net contents 1 litre

Resene Strip-Off is an effective, low odour paint stripper, free from methylene chloride, caustic soda and other strong alkalis. Resene Strip-Off is non-drip and suitable for removing paint from common household items.

- Strips a wide range of paints.
- Penetrates deep into paint film.
- Active for up to 4-6 hours.
- Non-drip formula.
- Can be applied on vertical surfaces.
- Lower hazard – methylene chloride free.
- Clean up in water and detergent.

Preparation

- Ensure surface is dry prior to application of Resene Strip-Off.
- Roughen old paint with coarse sandpaper to assist in the penetration of Resene Strip-Off.
- **All sanding dusts can be harmful. Always wear appropriate protection. Seek expert advice if working with lead, chromate or asbestos based materials or surfaces.**

Application

- Although Resene Strip-Off is a lower odour material it is a very powerful solvent; wear goggles and solvent resistant gloves.
- Apply a full flowing coat to the surface by brush to thoroughly wet the surface. Leave Resene Strip-Off in this wet condition for at least 30 minutes before testing. If the paint removes easily, use a broad knife to scrape the surface.
- If the paint is still adhering firmly, leave another 30 minutes before testing again. A softening period of up to, or even exceeding, one hour may be necessary.
- Do not allow Resene Strip-Off to dry on the surface.
- Scrub with a nylon pot scourer to assist in the stripping process.
- After stripping the surface to ensure complete removal of the residues, scrub down with weak detergent and water.
- Allow the surface to dry for 24 hours and lightly sand. Wipe off sanding dust.
- Clean brushes using detergent and water.

Be PaintWise

or tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.

COMBUSTIBLE LIQUID

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Quick check

Use on: Enamels, varnishes, acrylics, automotive paints and two pack products. Do not use on vinyl, rubber, plasterboard and fibreglass surfaces.

Coverage: 1-2 square metres per litre per coat.

Stripping time: 30 minutes to 2 hours depending on paint type.

Usual number of coats: One. A second application may be required to remove stubborn paint layers.

Application method: Brush.

Thinning: Do not thin.

Clean up: Wash surfaces with weak detergent and cold water to remove residue.

Colour: Pale amber.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

Read the appropriate Product Data Sheet and Safety Data Sheet before use.

Please ensure that the colour in this container is the same as selected. Resene accepts no responsibility for the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Ltd
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Ltd
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz

