

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

WARNING

Read label before use. Keep out of reach of children. Harmful if swallowed. Causes mild skin irritation. Causes serious eye irritation. Harmful to terrestrial vertebrates.

PRECAUTIONS

DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Wear protective gloves and clothing, eye and face protection. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor, or physician if you feel unwell.

IF ON SKIN (or hair): If skin irritation occurs, get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical advice or attention.

When seeking medical advice take this container with you.

Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: Ethylene Glycol Monobutyl Ether 280-480 gms/L.

SPILLS

Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to run off into waterways. Refer to local waste management authority.

Summit Roof Spray Additive

net contents 500ml

Resene Summit Roof Spray Additive is specially formulated to extend open time, improve flow and levelling, and to achieve an integrated paint film when Resene Summit Roof paint is airless spray applied to an existing dark roof paint colour or when the surface is too hot to touch.

Addition rates (maximum)

- 80ml per 4 litres Resene Summit Roof paint
- 200ml per 10 litres Resene Summit Roof paint

In every case it is recommended that the appropriate Safety Data Sheet is consulted prior to application.



COMBUSTIBLE LIQUID

Keep away from heat, sparks, open flames and hot surfaces. No smoking

Please ensure that use of this product is compatible with the paint. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960

Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600

Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using de-inkable toners for recycling with no solvent emissions.



9 418022 066279