

net contents
10 litres

LL3166510 5/13

WARNING

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE or doctor/physician if you feel unwell.

IF ON SKIN (or hair): Remove/take off all contaminated clothing and wash before re-use. Wash skin with plenty of soap and water/shower. If skin irritation or rash occurs get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists, get medical attention/advice.

When seeking medical advice take this container with you. Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use in covering graffiti.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

TagCover

waterborne graffiti covering paint

exterior/interior

KEEP OUT OF REACH OF CHILDREN



WHITE

Resene TagCover is a range of waterborne satin paints formulated to provide a budget friendly paint system to cover graffiti.

Application

Ensure surfaces are clean and dry, free from dirt, dust and loose material, oil, grease and mould.

- **Coverage:** 12 square metres per litre per coat. Coverage will vary dependent on surface porosity and profile.
- **Dry time (minimum):** 30 minutes at 18°C. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period.
- **Recoat time (minimum):** 2 hours. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.
- **Usual number of coats:** 1-2 depending on surface and finish required.
- **Before use:** Stir with a wide flat stirrer prior to application. Do not shake or brush excessively.
- **Application method:** Synthetic fibre roller, brush, speed brush or spray.
- **Thinning and clean up:** Water.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.



TagCover SDS

Resene

the paint the professionals use



TagCover TDS

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.