

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.

Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

DANGER
KEEP OUT OF REACH OF CHILDREN

Resene Thinner No.3A

LL8030004 12-24

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects. Harmful to terrestrial vertebrates.

PRECAUTIONS

DO NOT BREATHE MIST, VAPOURS OR SPRAY. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye or face protection. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of water. If skin irritation or rash occurs get medical advice or attention. Take off immediately all contaminated clothing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTRE, doctor or first aider.

IF BREATHING DIFFICULT GET MEDICAL ATTENTION IMMEDIATELY.

net
contents
4 litres

When seeking medical advice take this container with you. If exposed or concerned get medical advice or attention. If exposed or concerned call a Poison Centre. Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.
NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.
CONTAINS: Isopropanol 160-340 g/L, Xylene 240-420 g/L, Methyl Isobutyl Ketone 160-340 g/L.
For use as a paint thinner.

SPILLS

Eliminate all sources of ignition. Ventilate area, avoid breathing vapours.

Use absorbent clean-up materials, such as fire retardant treated sawdust or diatomaceous earth to dike and contain spill. Scrape up and remove.

Collect and seal in properly labelled drums. Refer to local waste management authority. Keep out of public sewers and waterways.

FIRE

Blanket flames with dry chemical, carbon dioxide or foam. Wear self-contained breathing apparatus. Closed containers may explode when exposed to extreme heat.

The storage of flammable goods may require certification/licencing by the appropriate agency.

Consult the local Dangerous Goods Inspectorate.

Dispose of unwanted material in accordance with Local Body Regulations.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.



UN NO. 1263 – PAINT
RELATED MATERIAL

**HIGHLY FLAMMABLE LIQUID
AND VAPOUR**

Keep away from heat, hot surfaces, sparks,
open flames and other ignition sources.
No smoking.

Resene

the paint the professionals use



In Australia: Resene Paints (Aust) Ltd
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Ltd
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz

Quick check

Thinner	Product
No.2	Lusta-Glo, Room Velvet, Super Gloss, Sureseal
No.3A	ArmourZinc 125
No.4	ArmourX Adhesion Etch Primer
No.5	Armourcote 608, Steel Fab
No.6	Alumastic, Armourchlor HB-F (spray application), Armourcote 510, ArmourX Cold Galv, ArmourX IF 503
No.7A	Uracryl 400 Series (spray application)
No.8	Uracryl 400 Series (brush/roller application)
No.9	Zincilate 11
No.10	ArmourX Rust-Arrest (brush/roller application), Slow Retarder
No.11	Armourchlor HB-F (brush/roller application), Armourcote 515 (application above 35°C or over zinc rich primers), ArmourX Cold Galv, Medium Retarder, Steel Fab
No.12	Armourcote 220 and 515, ArmourX Rust-Arrest (spray application), ArmourZinc 120, Universal Cleaner

Read the appropriate Safety Data Sheet before use.

For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

