

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.  
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 980 mL  
(white, contents greater when tinted)

LL1880201 10-24

KEEP OUT OF REACH OF CHILDREN

### SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland, with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation. Harmful to aquatic life with long lasting effects.

### PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Avoid release to the environment.

### FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTRE, doctor or first aider.

When seeking medical advice take this container with you.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126  
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)  
or call Resene 0800 737 363.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D322.

If using this product tinted to a Resene CoolColour™, see Data Sheet D322C.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grass/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways. See [resene.com/cleanup](http://resene.com/cleanup) for cleaning instructions.

# Resene

## Walk-on

### flooring and paving paint

exterior/interior waterborne



WHITE

Resene Walk-on is based on tough acrylic resins to give maximum abrasion resistance in a single pack satin finish. The surface finish of Resene Walk-on is designed to reduce the hazard of slipping. Mix with Resene Anti-Slip Grip Additive for extra slip resistance.

### Preparation

- Ensure the surface is in sound condition, dry and free from dirt, dust, loose material, oil (including mineral oil-based wood finishes or similar) and salt.

- Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).

- Allow new concrete to cure for a minimum of 28 days.

- Diamond grind or acid etch concrete floors. If either is impractical prime the prepared surface with Resene ConcreteSeal 3 in 1 (see Data Sheet D409) but only in the absence of a curing membrane.

- Water blasting is the best surface preparation if Resene ConcreteSeal 3 in 1 is to be used.

- Remove oil and grease using Resene Paint Prep and Housewash. If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Efflorescence on masonry must be treated.

- If you are coating new bare bitumen, clean the surface using Resene Heavy Duty Paint Prep and Oil Remover (see Data Sheet D816). Machine scrubbing will enhance removal of dirt and contaminants. Rinse clean with water and allow to dry thoroughly.

- Thoroughly scrape and sand to remove any weakly adhering or flaking paint and to provide a key for good adhesion.

- Fill cracks and holes in timber with an appropriate filler after priming.

- Round all sharp timber edges and sand back loose cellulose fibres. Thoroughly sand or treat any bare timber surface that has been left exposed to the weather for more than one week with Resene TimberLock (see Data Sheet D48).

- All sanding dusts can be harmful. Always wear appropriate protection. Seek expert advice if working with lead, chromate or asbestos based materials or surfaces.

- Test for moisture by taping a 30cm square of clear plastic to the concrete floor. If moisture appears under the plastic after 48 hours, repeat test until plastic is clear.

- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

restoration of badly weathered timber surfaces.

- Prime exterior timber with Resene Wood Primer (see Data Sheet D40).
- Use Resene Quick Dry as the first coat on Matai, Spotted Gum, Totara, fibre and particle board.

- On old or weathered cementitious substrates seal with one coat of Resene Walk-on thinned 10% with water and allow 24 hours before applying finish coats.

- Prime bitumol decking with Resene Membrane Primer (see Data Sheet D49).

### Topcoat

- Apply two coats allowing sufficient dry time between coats. Allow at least 12 hours' dry time after the final coat before subjecting the primed area to light foot traffic. Allow 48 hours for full cure.

- For interior use, especially where dark colours are planned, apply a coat of Resene Concrete Wax for extra durability.

- For extra slip resistance, add one pack of Resene Anti-Slip Grip Additive per litre of Resene Walk-on. Follow the coat of Resene Anti-Slip Grip Additive modified coating with one coat of standard (unmodified) Resene Walk-on.

- Maintain good ventilation throughout the drying and curing period to ensure the paint is properly cured. Poor ventilation may inhibit curing and performance.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet.

### Quick check

**Use on:** Interior and exterior domestic surfaces and light industrial surface areas.

**Gloss level:** Satin.

**Typical coverage:** 10 square metres per litre per coat. The spreading rate recommended for this product will achieve hiding in two coats for most colours. Coverage may vary depending on substrate, colour, application technique and weather/temperature conditions. See the Resene website for more information.

**Dry time (minimum):** 1 hour at 20°C. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

**Recoat time (minimum):** 2 hours at 20°C.

**Primer required:** Yes dependent on surface.

**Usual number of coats:** Two.

**Application method:** Brush, roller or spray.

**Thinning:** In hot conditions thin with up to 5% Resene Hot Weather Additive to slow drying.

**Clean up:** Water.

**Colour range:** Colours off white, pastel, light, mid and ultra deep tone.

Also available as Resene Walk-on CoolColour to help reflect heat from exterior surfaces. Application of a Resene CoolColour will reflect more heat than the same colour made using non-cool pigmentation and reduce heat related stress on the substrate; it will not make the painted surface cool to touch. Check with Resene staff whether a Resene CoolColour is right for your project.

**Before use:** Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

Read the appropriate Product Data Sheet and Safety Data Sheet before use.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



Walk-on SDS

# Resene

the paint the professionals use



Walk-on TDS

In Australia: Resene Paints (Aust) Ltd  
7 Production Ave, PO Box 918, Ashmore City, QLD 4214  
Ph 1800 738 383 Visit [resene.com.au](http://resene.com.au)

In New Zealand: Resene Paints Ltd  
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045  
Ph (04) 577 0500 Visit [resene.co.nz](http://resene.co.nz)