

# WARNING

KEEP OUT OF REACH OF CHILDREN

# Resene

# Woodsman Whitewash

exterior

Also  
available in  
Greywash

A-LL2295004 9/18

#### SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. May cause an allergic skin reaction. Suspected of damaging fertility or unborn child. Harmful to aquatic life with long lasting effects.

#### PRECAUTIONS

AVOID BREATHING MISTS, VAPOURS, OR SPRAYS.. Obtain special instructions before use. Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Wear protective gloves and clothing, eye and face protection. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

#### FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

If exposed or concerned, get medical advice or attention.

When seeking medical advice take this container with you.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126

or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)

or call Resene 0800 737 363.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D57W.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Woodsman Whitewash is an exciting way of achieving a whitewash effect on new or weathered exterior timber. This product can also be tinted to achieve a greywash effect, which can be used on its own or with tinted Resene Waterborne Woodsman stains for additional greywash options.

#### Preparation

• Treatment with Resene Timber and Deck Wash (see Data Sheet D813) is recommended for all substrates to remove dirt, natural stains and enhance the degree of product penetration. Ensure surfaces to be stained are dry, free from dust, dirt and loose material.

• If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).

• For repaints of existing penetrating stains remove any gross contamination and loose cellulose fibres.

• **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

• Always colour test first to check your choice of Resene Woodsman Whitewash colour gives the result you want on the actual timber you are staining.

• Consult your Resene ColorShop or Reseller for advice on coating severely weathered surfaces, exotic timbers, non-standard timbers and exterior doors and windows.

• Stains are not acceptable finishes for substrates that will be used in the collection of rainwater for drinking purposes. Only products that are expressly recommended for use in rainwater collection should be considered.

• This product may be used to stain a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

#### Precautions

• Contains powerful fungicides.

• Avoid skin contact.

• Will not prevent checking of plywood.

• Where alkaline cleaners (including Resene Moss & Mould Killer) are used in the preparation of the substrate, ensure that any residue is removed by hosing down with clean water. These residues can affect film formation and, subsequently, durability.

• Always test the finish you plan to use with a Resene testpot. If you see tannin staining occurring then change to either a standard solventborne Resene Woodsman Wood Oil Stain system (choosing from the colour range available for that product) or a solid colour painted system with an enamel primer, such as Resene Wood Primer (see Data Sheet D40). Tannin staining most commonly occurs with application to flat sawn cedar cladding and will tend to wash out over two to three months of direct weathering.

#### Application

• Before use and regularly during use, stir well with a wide flat stirrer.

• Apply one full coat and allow to dry before applying second coat if required.

• All faces of the timber should be treated with special attention to end grains.

• For new work apply the second coat preferably before one week. Protection begins after full system is applied.

• Will not penetrate through existing coatings or very hard latewood bands. For best results wipe excess Resene Woodsman Whitewash off with a dry, absorbent, lint-free cloth rubbing along the grain.

• Will typically require maintenance after two to three summers. Performance is related to the depth of colour applied and exposure level with north facing elevations requiring earlier attention to maintenance. Light applications, light colours and dressed surfaces may require maintenance sooner, while heavier applications, darker colours and rough sawn

surfaces will require less maintenance.

#### Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.

#### Colours available



Additional greywash effects can be achieved by using a tinted Resene Colorwood stain as the first coat.



Woodsman Whitewash SDS

# Resene

the paint the professionals use



Woodsman Whitewash TDS

**In Australia:** Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Ph 1800 738 383 Visit [www.resene.com.au](http://www.resene.com.au)

**In New Zealand:** Resene Paints Limited  
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045  
Ph (04) 577 0500 Visit [www.resene.co.nz](http://www.resene.co.nz)

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

#### Quick check

**Use on:** Timber surfaces.

**Gloss level:** None. Fully penetrating over bare timber.

**Typical coverage:** (a) Dressed timber:

1st coat, 10-12 square metres per litre,

2nd coat, 12-14 square metres per litre.

(b) Rough sawn timber:

1st coat, 4-6 square metres per litre,

2nd coat, 9-11 square metres per litre.

(c) Badly weathered timber:

1st coat, 3-4 square metres per litre,

2nd coat 5-7 square metres per litre.

**Dry time (minimum):** 45 minutes. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

**Recoat time (minimum):** 2 hours.

**Primer required:** No.

**Usual number of coats:** Two. Will require maintenance after two to three summers.

**Application method:** Brush or roller.

**Thinning and clean up:** Do not thin. Clean up with water when wet or mineral turps when dry.

**Colour range:** Whitewash and greywash.

**Before use:** Stir well with a wide flat stirrer and also stir during application.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



9 418022 105608 9

WHITEWASH