

net contents 1 litre  
tinter included

LL22401 11/17

#### SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Harmful to aquatic life with long lasting effects.

#### PRECAUTIONS

AVOID BREATHING MISTS, VAPOURS OR SPRAYS. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Use only outdoors or in a well ventilated area. Wear protective gloves and clothing, eye and face protection. Use personal protective equipment as required. Ground or bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use only non-sparking tools. Avoid release to the environment. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

#### FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor, physician or first aider.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention. Remove contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing breathing difficulties immediately seek medical attention.

If exposed or concerned get medical advice or attention.

If medical attention is required: have product container or label at hand.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)

or call Resene 0800 737 363.

CONTAINS: 3-Iodo-2-propynyl Butyl Carbamate 1-10 gms/L, Diethylene Glycol Monomethyl Ether 1-10 gms/L, Naphtha Petroleum, heavy, Hydrodesulfurised 10-100 gms/L, Ethylbenzene 1-10 gms/L, Xylene 10-100 gms/L, 1,2,4-trimethyl Benzene 100-200 gms/L, Isopropyl Benzene - Cumene 10-100 gms/L, Naphtha Petroleum, light aromatic Solvent 10-100 gms/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D57.

If exposed or concerned get medical attention.

**SPILLS:** Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or mineral turps. Do not allow mineral turps to enter any drains. Refer to your local Council for disposal of dirty mineral turps.

**FIRE:** Use foam, carbon dioxide or dry chemical powder.

# WARNING

KEEP OUT OF REACH OF CHILDREN

# Resene

## Woodman Wood Oil Stain exterior



TINT  
BASE

Resene Woodman Wood Oil Stain is a solventborne wood oil stain matching the needs of timber with your desire to achieve the most natural appearance possible. Suitable for exterior timber including trafficable areas such as decks.

#### Preparation

• Treatment with Resene Timber and Deck Wash (see Data Sheet D813) is recommended for all substrates to remove dirt, natural stains and enhance the degree of product penetration.

• Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt.

• Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).

• If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).

• Any bare timber surface that has been left exposed to the weather for more than one week should be thoroughly sanded.

• For repaints of existing penetrating stains remove any gross contamination and loose cellulose fibres.

• All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.

• Always colour test first to see your choice of Resene Woodman Wood Oil Stain colour gives the result you want on the actual timber you are coating.

• Consult your Resene ColorShop or Reseller on coating severely weathered surfaces, exotic timbers, non-standard timbers and exterior doors and windows.

• Wood oil stains are not acceptable finishes for substrates that will be used in the collection of rainwater for drinking purposes. Only products that are expressly recommended for use in rainwater collection should be considered.

• This product may be used on a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

#### Application

• Any movement of weatherboards (board dimensional changes) will be exacerbated with darker colours. A CoolColour version will reflect more heat compared to the standard colour. However, this will reduce the potential for dimensional changes rather than necessarily eliminate it. If weatherboards move uncoated board or previous coats of stain may become visible. This is not a stain fault, but due to excessive movement in the weatherboards. If in doubt, use a lighter colour option to minimise heat build-up.

• Before use and regularly during use, stir well with a wide flat stirrer.

• Saturate the surface with Resene Woodman Wood Oil Stain.

• All faces of the timber should be treated with special attention to end grains.

• Resene Woodman Wood Oil Stain will not penetrate existing coatings or very hard laterwood bands. Wipe excess Resene Woodman Wood Oil Stain off with a dry, absorbent, lint free cloth rubbing along the grain.

• Contains powerful fungicides. Avoid skin contact and wear gloves when wiping off any excess.

• For new work apply the second coat after 24 hours and preferably before one week. Protection begins after full system is applied.

• Will not prevent checking of plywood.

• Will typically require maintenance after two summers. Performance is related

to the depth of colour applied. Light applications, light colours and dressed surfaces may require maintenance sooner, while heavier applications, darker colours and rough sawn surfaces will require less maintenance.

#### Precautions

• Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d).

#### Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



UN NO. 1263 - PAINT RELATED PRODUCT

**FLAMMABLE LIQUID AND VAPOUR**

Keep away from heat, sparks, open flames  
and hot surfaces. No smoking.



Woodman Wood  
Oil Stain SDS

**Resene**

the paint the professionals use



Woodman Wood  
Oil Stain TDS

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Phone 1800 738 383 Fax 1800 064 960  
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited  
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Phone (04) 577 0500 Fax (04) 577 0600  
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

## Quick check

**Use on:** Exterior timber surfaces.

**Gloss level:** None. Fully penetrating.

**Typical coverage:**

(a) Dressed timber: 1st coat, 10-12 square metres per litre; 2nd coat, 12-14 square metres per litre; apply a 3rd coat, 12-14 square metres per litre after 3-6 months.

(b) Rough sawn timber: 1st coat, 4-6 square metres per litre; 2nd coat, 9-11 square metres per litre.

(c) Badly weathered timber: 1st coat, 3-4 square metres per litre; 2nd coat 5-7 square metres per litre.

**Dry time (minimum):** 24 hours. Drying is slowed by low temperatures and high humidity.

**Recoat time (minimum):** 24 hours.

**Primer required:** No.

**Usual number of coats:** Two. Will require maintenance after two summers.

**Application method:** Brush, roller or spray.

**Thinning and clean up:** Do not thin. Clean up with mineral turps.

**Colour range:** Standard colours, refer Resene Exterior woodcare colour chart.

Also available as Resene Woodman CoolColour to help reflect heat from exterior surfaces. Check with Resene staff whether a Resene CoolColour is right for your project.

**Before use:** Stir well with a wide flat stirrer and also stir during application.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 365 (NZ) or visit the Resene website.